

**Belden P/N 50106FLB**  
**SWB Armoured Industrial Category 6 F/UTP LSZH Cable**



### Applications

Industrial Ethernet cables are used for interconnecting Industrial Ethernet Switches, IP controllers, media converters, distributed control system, programmable logic controller and transmitting industrial protocol data signals. These cables are suitable for transmitting 100BASE-TX Gigabit Ethernet, 100BASE-T Ethernet, 100BaseVG ANYLAN, 155ATM, 622ATM, RS-422, 250MHz Category 6, EtherCAT. These are highly durable & ruggedized cables for both indoor and outdoor use meeting IEC 60332-3-24 and IEC 60754-1 & 2

### General Reference Standards

- IEC/ISO 11801, IEC 61156-5 & TIA-568 -C.2
- PoE: IEEE 802.3bt Type 1, Type 2, Type 3, Type 4
- IEC 60332-3-24, 60754-1, 60754-2, 61034-2
- EU RoHS

<b>Physical Characteristics</b>	
Conductor Size	23 AWG
Conductor Material	Solid Bare Copper
Insulation Material	PO - Polyolefin
Number of Pairs	4 Pairs
Overall cabling filler	Central Spline
Shield	Aluminium Foil -Polyester Tape
Shield Drain Wire	Solid Tinned Copper
Inner jacket Ripcord	Optional
Inner Jacket	LSZH - Low Smoke Zero Halogen
Armor	Galvanized Steel Wire Braid Armor (SWB)
Outer jacket Ripcord	Optional
Outer Jacket	LSZH - Low Smoke Zero Halogen
Nom. Diameter	10.5 mm
Suitability	Indoor and Outdoor
UV Resistance	Yes
Oil Resistance	Yes
Flame Retardant	IEC 60332-3-24
Other Specifications	ISO/IEC 11801 Cat 6 IEC 61156-5 Cat 6 TIA/EIA 568-C.2 Cat 6

<b>Electrical Characteristics</b>	
Max. Conductor DCR @ 20°C	9.38 Ω/100m
DCR Unbalance @ 20°C	Max. 5%
Nom. Mutual Capacitance @ 1KHz	5.6 nF/100m
Max. Capacitance Unbalance	330 pF/100m
Characteristic Impedance	100 ± 15 Ω
Max. Delay @ 100MHz	538 ns/100m
Max. Delay Skew	45 ns/100m
Max. Operating Voltage	300V RMS

<b>Mechanical Characteristics</b>	
Operating Temperature Range	-20°C To +75°C
Bulk Cable Weight	141 kg/km
Max. Recommended Pulling Tension	110 N
Min. Bending Radius (Install)	84 mm

<b>Other Properties</b>	
Halogen Content per IEC 60754-1	≤ 5 mg/g
Acid Gas Emission pH per IEC 60754-2	≥ 4.3
Acid Gas Emission Conductivity per IEC 60754-2	< 10 µs/mm
Smoke Density as per IEC 61034-2	≥ 60% Light Transmittance

# Technical Data Sheet

## Industrial Armored Category 6 Shielded LSZH Cable

### Electrical Characteristic - Premises:

Frequency (MHz)	Max. Attenuation (dB/100m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. Return Loss (dB)	Min. ACRF (dB)	Min. PSACRF (dB)
1	2.0	74.3	72.3	20.0	67.8	64.8
4	3.8	65.3	63.3	23.0	55.8	52.8
8	5.3	60.8	58.8	24.5	49.7	46.7
10	6.0	59.3	57.3	25.0	47.8	44.8
16	7.6	56.2	54.2	25.0	43.7	40.7
20	8.5	54.8	52.8	25.0	41.8	38.8
25	9.5	53.3	51.3	24.3	39.8	36.8
31.25	10.7	51.9	49.9	23.6	37.9	34.9
62.5	15.4	47.4	45.4	21.5	31.9	28.9
100	19.8	44.3	42.3	20.1	27.8	24.8
155	25.2	41.4	39.4	18.8	24.0	21.0
200	29.0	39.8	37.8	18.0	21.8	18.8
250	32.8	38.3	36.3	17.3	19.8	16.8

### Put Ups & Colours:

Stock Code	Cable Description	Put Up (MT)	Jacket Colour	Ship Weight (kg/reel)
50106FLB 006305M	4P X 23 AWG PO LSZH FTP CAT6 SWB ARMOR	305	BLU	43
50106FLB 008305M	4P X 23 AWG PO LSZH FTP CAT6 SWB ARMOR	305	GRY	43
50106FLB 010305M	4P X 23 AWG PO LSZH FTP CAT6 SWB ARMOR	305	BLK	43



Revision Number:4

Revision Date: 12/21/2023

© 2023 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.