
DALI Relay Module

DALL CE PROHS

Important: Read All Instructions Prior to Installation

Function introduction



Product Data

Input			Output, relay			
DALI control input	DALI consumption		Switching voltage AC	Switching voltage DC	Current	Type of contact
1	< 3mA	1	Max. 250V	Max. 30V	Resistive load: max. 4.3A Capacitive load: max. 1.3A Inductive load: max. 4.3A	1 changeover

	Compatible Load Types				
Load Symbol	Load Type	Maximum Load			
	Resistive loads Conventional incandescent and halogen light sources	1000W @ 230VAC 500W @ 110VAC			
	Capacitive loads Fluorescent tube lamp (compact / with electronic ballast), electronic transformer, LED	300W @ 230VAC 150W @ 110VAC			
•	Inductive loads Ferromagnetic transformers	1000W @ 230VAC 500W @ 110VAC			


- 70040043
- DALI relay module
- DALI bus powered, no extra power supply required
- 1 DALI address can be assigned by DALI master controller
- · Control of one standard contactor
- · Compact relay module for controlling a standard contactor via DALI
- Loads that do not have a DALI input can therefore be integrated in the DALI circuit
- The loads can be switched on and off via DALI
- Compatible with universal DALI systems and master controllers in the market
- · Mini Size, easy to be Installed into a standard wall box
- 5 years warranty
- Waterproof grade: IP20

Safety & Warnings


- DO NOT install with power applied to device.
- DO NOT expose the device to moisture.

Wiring diagram

(1) Switching of 100-240VAC load



(2) Switching of 12/24VDC load



Operation

Setting DALI Address:

1 DALI address can be assigned by DALI Master controller automatically, please refer to user manuals of compatible DALI Masters for specific operations.

Product Dimension

