
## NSYBVS800

## Vertical bar support up to 3200 A 800x800 mm



Main	
Range	Spacial
Accessory / separate part category	Busbar accessory
Product or component type	Busbar support
Application	Prisma application Multi-purpose
Enclosure nominal dimensions	-
Mounting location	On structure of enclosure
Busbar position	Vertical
Range compatibility	Spacial SF Linergy LGYE Linergy BS Spacial SFP Prisma PH Spacial SFM

Complementary

Complementary		
Cubicle-device connection	Linergy LGYE lateral busbar - fixed	
	Linergy BS lateral busbar - fixed	
Device composition	Fixing elements	
	1 metal support	
	2 insulating bar support	
Quantity per set	Set of 1	
Material	Bar support: plastic	
	Metal support: steel	
Fixing mode	By fixing element	
Width	750 Mm fixing centers:	
	800 mm nominal:	
Depth	39 mm	
[In] rated current	3200 A	

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months	