

Eaton ABC-20-R

Catalog Number: ABC-20-R

Eaton ABC series Fast-acting fuse 20A, 250 Vac, 125 Vdc, 32 Vac (self certified), ABC-20-R



General specifications

| | |
|--|----------------------|
| Product Name | Catalog Number |
| Eaton Bussmann series ABC fast-acting fuse | ABC-20-R |
| | UPC |
| | 051712646222 |
| EAN | Product Length/Depth |
| 5027590226479 | 1.25 in |
| Product Height | Product Width |
| 0.25 in | 0.25 in |
| Product Weight | Compliances |
| 0.008 lb | CE Marked |
| | RoHS Compliant |

Catalog Notes

Ceramic body allows for higher amp/volt rating combinations.

Product specifications

Fuse indicator

Non-indicating

Interrupt rating

10 kAIC at 125 Vdc

1 kAIC at 125 Vac

400 AIC at 250 Vac

Connection

Ferrule end x ferrule end

Response time

4 hr at 100%, 60 min at 135%, 120 sec at 200%

Quantity

5

Material

Nickel-plated brass endcaps

Ceramic tube

Melting (I²T)

Typical pre-arc: 550.8

Amperage Rating

20 A

Voltage drop

0.1 mV typical

Resistance

0.00366 ohms DC cold

Type

Electronic

Voltage rating

250 Vac, 125 Vdc, 32 Vac (self certified)

Application

Electronic circuits

Resources

PEP Eco-passport

EATO-00033-V01.01-EN

Specifications and datasheets

Eaton Specification Sheet - ABC-20-R

Eaton ABC fast-acting ceramic tube fuses data sheet



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)