



REACH SVHC161

ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance:10ohm
3. Insulation Resistance:5Mega ohm
4. Hipot test:300V/10ms

USB 3.1 CM	Pin Description	USB3.0 AF	Pin Description
A1,B1,A12,B12	GND	4,7	GND
A4,B4,A9,B9	VBUS	1	VBUS
A6	Dp1	3	D+
A7	Dn1	2	D-
A5	CC		
B5	Vconn		
A2	SSTXp1	9	SSRX+
A3	SSRXn1	8	SSRX-
B11	SSTXp1	6	SSTX+
B10	SSRXn1	5	SSTX-
SHELL	Shield	SHELL	Shield

5.1KΩ

NO.	DESCRIPTION	Q'TY	UNIT
3	USB3.1 C TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F	1	pcs
2	55P PVC MOLD BLACK IN COLOR	1	pcs
1	USB3.0 A TYPE FEMALE SHELL PLATED:NICKEL CONTACT:G/F	1	pcs

REV.	DESCRIPTION	RS P/N	DATE
		3008950537	15/02/01



UNLESS OTHERWISE SPECIFIED TOLERANCE		FILE NAME:
ANG.	±5°	
0.	±0,5	
.0	±0,3	
.00	±0,2	
SCALE:	NONE	
	UNIT: mm	
DRAWN	TANG	15/02/01
CHECKED	ERIC	15/02/01
APPROVED		
SIZE	REV.	
A4	A	