

FEATURES

- Miniature DC SSR mounted on Din EN adapter.
- 60VDC 8 Amp.
- Control voltage 4.25VDC – 32VDC
- Isolation input / output 4000 VACrms
- Operating Temp -20°C to 80°C (-4°F - 176°F)
- Blocking Voltage 60VDC
- Dropout Voltage 1 VDC
- Minimal Operational Load 1mA
- Surface mount technology
- Switching Frequency <100Hz
- Off state leakage current <0.01mADC
- Potting compound
Flame retardant
Silicone rubber.
Extends life, flexible encapsulation

RS PRO DC switching SSR 60VDC 8Amps Control 4.25 - 32 DC with base

RS Stock No.: 2303313



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Family Name

Product Description

- The DC switching relay is used in applications where there is a need for fast switching of small DC loads with a high input/output insulation of more than 4000VACrms. The DC switching relay always switches on and off in accordance with the applied control voltage
- Applications: - Heaters, Motors, Valves or Solenoids

General Specifications

Miniature Din Rail mount SSR	8 Amp, 60v SSR mounted on Din EN Adapter
-------------------------------------	--

Mechanical Specifications

SSR 43mm * 25.4mm*10.5mm

Electrical Specifications

8 Amp, 60VDC

Additional Information

EAN	5350035408247
Custom Tariff Number	85362010

Approvals

Declarations	MFR Declaration of Conformity
Hazardous Area Certification	
Standards Met	

