




- Material : PA6 V-2 Acc. To UL94 Flammability Class
- Sealing Material: EPDM
- IP Grade: clamping range, O-ring, IP68
- Temperature Limited: -40°C-100°C , short- term 120°C
- Products Feature: Connection is more smoothly & closely with double-thread & O-ring groove. Protect connection by using improved protective sealings



Thread Spec. Specification	RAL7035 Color	Cable range	Thread OD (AG)	Thread Length (GL)	Height (H)	Spanner	Reference
M12A×1.5	Grey	3-6.5	12	8	21	15	9HT RSKP-M12A-GY-PA6-PM
M16A×1.5	Grey	4-8	16	8	22	19	9HT RSKP-M16A-GY-PA6-PM
M20A×1.5	Grey	6-12	20	9	27	24	9HT RSKP-M20A-GY-PA6-PM
M25A×1.5	Grey	13-18	25	11	31	33	9HT RSKP-M25A-GY-PA6-PM
M32A×1.5	Grey	18-25	32	11	39	42	9HT RSKP-M32A-GY-PA6-PM
M40A×1.5	Grey	22-32	40	13	48	53	9HT RSKP-M40A-GY-PA6-PM
M50A×1.5	Grey	32-38	50	15	49	60	9HT RSKP-M50A-GY-PA6-PM
M63A×1.5	Grey	37-44	63	15	49	65/68	9HT RSKP-M63A-GY-PA6-PM

Note:

1) Made under OEM arrangement by reputable cable gland manufacturer