

Surface and anti-corrosion coating

Isolation Spray



Transparent insulating and finishing varnish based on acrylic resin

WEICON Isolation Spray is a transparent insulating and finishing varnish based on acrylic resin. It forms a flexible and resistant layer, which shows excellent adhesion to metal, glass, plastic or wood. It is resistant to UV radiation, acids, oils and lyes. It is moisture- and weather-resistant and stands out particularly due to its high dielectric strength. The spray protects against moisture as well as different vapours. It can be used as protective coating for circuit boards, on electrical connections, switches, switchboards, electronic components and coils, as universal sealant in electrical engineering or for the repair of insulations on electric motors, windings and frames.

Technische Daten

| | | |
|--------------------------|---|------------------------------|
| Odour | solvent | |
| Specific properties | high dielectric strength, material-compatible | |
| Silicone-free | yes | |
| Base | modified acrylic resin | |
| Consumption | ~2-3 | |
| dust-dry | 15 min. | |
| Cross cutting | DIN 53151/ISO 2409 | cross cut value 0-1 on steel |
| Density | 0,848 g/cm ³ | |
| Dielectric strength | DIN EN 60243 | 67,8 kV/mm |
| Solid content | 50 % | |
| spec. surface resistance | 7,59 | |
| Thermal conductivity | 20 °C DIN EN ISO 821 | 0,215 W/m·K |
| Temperature resistance | -40 (-40 °F) to +120 (+248 °F) | |
| Shelf life | 24 mon. | |

Processing

Clean and degrease surfaces with WEICON Surface Cleaner. Surfaces should be dry and free from dust and grease. Shake can before use, until the mixing pea is clearly audible. Apply the spray at room temperature (approx. +20 °C) evenly from a distance of approx. 25 cm.

Storage

Pressurized container. Protect from direct sunlight and temperatures above +50 °C.

Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes:

11551400 Isolation Spray, 400 ml

To the product detail page:



Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON Middle East L.L.C. United Arab Emirates phone +971 4 880 25 05 info@weicon.ae

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013 info@weicon.cz

WEICON GmbH & Co. KG (Headquarters) Germany phone +49 (0) 251 9322 0 info@weicon.de

WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@weicon.com

WEICON South East Asia Pte Ltd Singapore Phone (+65) 6710 7671 info@weicon.com.sg

WEICON Inc. Canada phone +1 877 620 8889 info@weicon.ca

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 info@weicon.es

WEICON Italia S.r.L. Italy phone +39 (0) 010 2924 871 info@weicon.it

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 info@weicon.com.tr