

# RF Cable Assembly

## SMA Straight Bulkhead Jack - SMP R/A Jack

**multicomp** PRO


**RoHS  
Compliant**



### Specifications

Cable Length	: 65mm / 2.56"
Connector Type A	: SMA Straight Bulkhead Jack
Connector Type B	: SMP Right Angle Jack
Cable Type	: RG-405
Impedance	: 50Ω
Frequency	: 0 – 13.5GHz
VSWR	: ≤ 1.1@1GHz
Return Loss	: ≥ 26.444dB@1GHz
Voltage Rating	: 335V RMS
Insulation Resistance	: 5,000MΩ Min.
Dielectric Withstanding Voltage	: 500V AC / 1 min. hold with no breakdown or flashover
SMA Contact Resistance	: Centre Contact: 3mΩ Max. Outer Contact: 2mΩ Max.
SMP Contact Resistance	: Centre Contact: 2mΩ Max. Outer Contact: 6mΩ Max.
Mating	: 1/4" – 36 Threaded Coupling / Snap-on Coupling
Durability	: 500 times
Body Material	: Beryllium Copper/Brass, Gold Plated
Centre Contact Material	: Beryllium Copper, Gold Plated
Insulating Material	: PTFE

### Diagram



### Part Number Table

Description	Part Number
RF Cable Assembly, SMA Straight Bulkhead Jack – SMP R/A Jack with RG-405, 65mm	MC002995

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro  
Farnell.com/multicomp-pro  
Element14.com/multicomp-pro

**multicomp** PRO