



### Main

|                           |              |
|---------------------------|--------------|
| Range of product          | Mita         |
| Product name              | Ultimate 60  |
| Product or component type | T-piece      |
| Provided equipment        | 2 tee bridge |
| Colour tint               | White        |
| Quantity per set          | Set of 1     |

### Complementary

|             |   |
|-------------|---|
| Fixing mode | By screws for extra security            |
| Material    | UPVC (unplasticized polyvinyl chloride) |

### Environment

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Standards                             | EN 50085-1: 2005<br>EN 50085-2-1 |
| Ambient air temperature for operation | -5...60 °C                       |
| Environmental characteristic          | RoHS compliant<br>REACH          |

### Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1826 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications