# **Solid State Relay**







## **Description**

The product is a single channel din-rail mounted module with 5A. Control voltage is 4-32V DC and isolation voltage is 4000VACrms with a high EMC capability and high inrush current.

#### **Features**

- Load Current: 0.1A to 5A
- · Din Rail Mounted
- DC Control
- LED Indication
- · High EMC Capability
- High Inrush Current

# **Applications**

Suitable for Automatic Equipment, Control System, Entertainment Equipment.

# **Technical Specification**

#### **Input Specifications**

Control Voltage Range : 4V DC to 32V DC

Min. Turn-On Voltage: 4V DCMin. Turn-Off Voltage: 1V DCMax. Input Current: 25mA

**Output Circuit** 

Max. Turn-On Time

Zero Crossing : 1/2AC Cycle + 1ms

Max. Turn-off Time : 1/2AC Cycle + 1ms

Max. Surge Current (@10 ms) (5A) : 60A

Max. Off-State Leakage Current [@ Rated Voltage] : 5mA

Max. On-State Voltage Drop [@ Rated Current] : 1.5Vrms

Min. Off-State dv/dt[@Maximum Rated Voltage] : 200V/µs

**General Information** 

Dielectric Strength Input/Output : ≧4000Vrms

Ambient Operating Temperature Range : -30°C to +80°C

Ambient Storage Temperature Range : -30°C to +100°C

Weight (Typical) : 55g


Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



# **Solid State Relay**




## Diagram





### **Thermal Curve**



## **Part Number Table**

Description	Part Number
SSR, DIN Module, 440V DC, 5A, 4-32V DC	MCDRA-1/KSD380D5-W(037)

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

