

Jack SMA Straight PCB Mount Receptacle

multicomp PRO



Specifications

Electrical

Frequency Range : DC-18 GHz
 Nominal Impedance : 50Ω
 Maximum Working Voltage : 500V
 Proof Voltage : 1,000V
 Maximum VSWR : 1.23

Materials

Bodies : Beryllium copper per ASTM B196 UNS C17300
 Centre contact : Beryllium copper per ASTM B196 UNS C17300
 Insulation : PTFE per ASTM D1457 and ASTM D1710


Mechanical

Interface in Accordance with : MIL-STD-348A

Environmental

Operating Temperature Range : -65°C to +165°C

Diagram



Dimensions : Millimetres (Inches)

Item	Description	Material	Finish
1	Body	Beryllium Copper	Gold 3µ Inches Min.
2	Insulation	PTFE	None
3	Centre Contact	Beryllium Copper	Gold 50µ Inches Min.

Part Number Table

Description	Part Number
Jack, SMA, PCB Tht, Str, Non-Mag	MP-60-04 TGG

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 Element14.com/multicomp-pro

multicomp PRO