



Main

| | |
|---------------------------|------------------|
| Range of product | WPS |
| Product or component type | Switched socket |
| Rated current | 32 A at 500 V AC |
| Poles description | 3P + N + E |

Complementary

| | |
|-----------------------------|--|
| Device mounting | Surface |
| Switch application | On/off switching |
| Outlet standard description | Round pin |
| Number of gangs | 1 gang |
| Material | PVC (polyvinyl chloride) UV stabilised |
| Cover frame colour tint | Grey |
| Height | 204 mm |
| Width | 101 mm |
| Depth | 104 mm |

Environment

| | |
|-------------------------|-----------------|
| IP degree of protection | IP66 |
| Motor M-rating AS3133 | M180 |
| Standards | GB/T 11918:2001 |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 11.5 cm |
| Package 1 Width | 10.4 cm |
| Package 1 Length | 20.8 cm |
| Package 1 Weight | 833.333 g |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 12 |
| Package 2 Height | 22.1 cm |
| Package 2 Width | 36 cm |
| Package 2 Length | 44.5 cm |
| Package 2 Weight | 10000 g |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 240 |
| Package 3 Height | 105 cm |
| Package 3 Width | 80 cm |

| | |
|------------------|----------|
| Package 3 Length | 120 cm |
| Package 3 Weight | 218000 g |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |