



Benefits

- Best fit to multi-purpose applications: be it accent lighting for display items or ambient lighting for a cosy look and feel
- Closely resembles look and feel of halogen spot
- High lumen output of 670lm, an ideal replacement for high powered 75w halogen

Application


Home


Hotel


Shopping Mall


Restaurant


Model	Item Description	W	PF	lm	lm/W	CRI	Beam	Life	Single Box (LxWxH)mm	Outer Box (LxWxH)mm	Packing Qty (PCS/CTN)
PAR16S1-7.2W-F-GU10	CLSV1 GU10 7.2W 4000K 36D HL	7.2	0.5	670	93	80	36°	20000	51*51*65	327*267*150	60
PAR16S1-7.2W-F-GU10	CLSV1 GU10 7.2W 6500K 36D HL	7.2	0.5	670	93	80	36°	20000	51*51*65	327*267*150	60

Application Conditions	
IP	IP20
Operating Temperature	-20~40°C
Application Temperature	25°C
Storage Environment	-25~50°C


Mechanical Properties	
Optical Material	PC
Housing Material	PBT
Finishing Colour	White

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC

Photometric Data



Dimensional Drawing



PAR16S1-7.2W-F-GU10