

Datasheet

RS PRO KKB-0115S is a tool for crimping non-insulated open-barrel terminals, 2.8 & 4.8/110 & 187 B/F crimp, 0.1 – 1.5 mm²


Stock No: 297-2979




Features & Benefits:

- High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force
- Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miss-crimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability

Indent Crimp Die Set



Crimp Profile



TECHNICAL DATA

Length: 204 mm/8.03"

Width: 22 mm/0.87"

Height: 76 mm/2.99"

Weight: 560 gr/1.23 lb

Wire size: 0.1-1.5 mm² / AWG 26-AWG 16

Crimp nest dimensions mm/mm²:

0.1 – 0.5 mm²/0.5 - 1 mm²/0.5 – 1.5 mm²

Crimp dimensions inch/AWG:

AWG 26 - 20/AWG 20 - 18/AWG 20 - 16

Connector: Uninsulated open barrel connectors

Description: For uninsulated 110 and 187 series open barrel tabs and receptacles.

Life span, cycles: 50,000