

FEATURES

- Quick connection and disconnection
- Large range to comply food norms
- Silicon free
- Operating temperature range is from - 15 °C to + 190 °C

RS PRO STRAIGHT MALE ADAPTOR (PARALLEL) -FOOD GRADE

RS Stock No.: 2312746



RS PROfessionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Pneumatic Quick Connect Couplings



Product Description

The RS PRO straight male adaptor (parallel) works in - 0.99 bar to 20 bar pressure range. It is mainly used in dairy, coffee machine, vending, food & beverage, medical, vacuum applications. It is available in brass with Food Grade coating. In combination with FEP tubes, it is the most demanded solution for the Food & Beverage market. Beacause of the special coating it can be used also in agressive environment.

RoHS and REACH compliant.

General Specifications

Material	Nickel Plated Brass		
Annlications	Lubrication System, Cooling System, Pneumatic		
Applications	Machinery Equipment		

Mechanical Specifications

Connection Type	Threaded, Tube
Tube Connection Size	6mm
Coupling Gender	Male
Threaded Connection	1/4 in Male
Thread Size	1/4in
Hose Barb Connection	6mm
Mounting Hole Diameter	16mm
Wrench Size1	13
Wrench Size2	4
Length	23.4mm

Pneumatic Quick Connect Couplings




Operation Environment Specifications

Minimum Operating Temperature	-15°C
Maximum Operating Temperature	190°C

Similar Products

Parameters	2312744	2312745		
Brand	RS PRO	RS PRO		
Connection Type	Threaded, Tube	Threaded, Tube		
Hose Barb Connection	4mm	6mm		
Coupling Gender	Male	Male		
Threaded Connection	1/8 in Male	1/8 in Male		
Thread Size	1/8in	1/8in		
Hose Barb Connection	4mm	6mm		
Mounting Hole Diameter	13mm	13mm		
Wrench Size1	10	13		
Wrench Size2	2	4		
Length	21mm	23.5mm		





Tube	Α	В	С	L	CH1	CH2	Pack.
6	1/4	7.1	16	23.5	13	4	10