



STRIPPING DIMENSION
SCALE 3:1

1.0 ELECTRICAL

- 1.1 FREQUENCY RANGE: DC-1 GHz
- 1.2 NOMINAL IMPEDANCE: 75 OHMS
- 1.3 VOLTAGE RATING: 500 VOLTS MAX.

2.0 MATERIALS

- 2.1 BODIES: BRASS PER JIS-C3604
- 2.2 CENTER CONTACT: BRASS PER JIS-C3604
- 2.3 INSULATION: TEFLON PER ASTM D1457 AND ASTM D1710
- 2.4 CRIMP FERRULE: BRASS PER JIS-C3604

3.0 FINISHES AND OTHERS

- 3.1 SEE BELOW TABLE FOR DETAILS.

4.0 MECHANICAL

- 4.1 FOR USE WITH RG179U OR SIMILAR STYLE CABLE
- 4.2 CABLE ATTACHMENT: OUTER: CRIMP, INNER: SOLDER
- 4.3 CRIMP SIZE REQUIRED: FERRULE: 3.5(138) HEX. CRIMP TOOL
5.5(218) HEX. CRIMP TOOL

5.0 ENVIRONMENTAL

- 5.1 OPERATING TEMPERATURE RANGE: -85° C TO +165° C

NO	DESCRIPTION	MATERIAL	Q'TY	FINISH
10	CRIMP FERRULE	BRASS	1	SILVER 70 μ" MIN.
9	INSULATION	TEFLON	1	NONE
8	CENTER CONTACT	BRASS	1	SILVER 70 μ" MIN.
7	BODY	BRASS	1	SILVER 70 μ" MIN.
6	WASHER	BRASS	1	SILVER 70 μ" MIN.
5	SPRING WASHER	SK-5	1	NICKEL
4	WASHER	BRASS	1	NICKEL
3	GASKET	SILICONE	1	RED
2	INSULATION	TEFLON	1	NONE
1	SHELL	BRASS	1	SILVER 70 μ" MIN.

APPROVED

by _____ DATE: _____



DESCRIPTION		BNC STRAIGHT PLUG CRIMP						
製圖	DRAWN	TOLERANCE	品名	13-55-6 T.S.S 179U	DATE	版次	REV.	
	Yoko							XX
檢圖	CHECK	UNIT	單位	DWG.NO.	13-0064			
	Arc					mm(in)		
認定	APPROVAL	SCALE	比例					
	Jenny			ANGLE ±5°	4:1			