



Main

Range of product	SpaceLogic KNX
Range	SpaceLogic KNX
Product or component type	Coupler
Product destination	KNX bus system
Bus type	KNX

Complementary

Total number of 18 mm modules	1
Wiring device mounting	DIN rail
Power supply input current	5 MA 3 mA
Material	PC
Communication port protocol	KNX KNX long frame KNX data security
Control type	2 push-buttons
Local signalling	3 LEDs
Function available	Supports KNX Secure
Market segment	Commercial Residential

Environment

IP degree of protection	IP20
Relative humidity	5...93 %
Ambient air temperature for storage	-25...70 °C
Ambient air temperature for operation	-5...45 °C
Standards	EMC directive EN 50491-3 EN 50491-5-2 EN 50491-5-3 EN 61000-6-2 EN 61000-6-3 EN 50581 : 2012

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.0 cm
Package 1 Width	7.0 cm
Package 1 Length	9.5 cm
Package 1 Weight	93.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	60
Package 2 Height	30.0 cm

Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	6.311 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins