

## FEATURES

- WATERTIGHT
- INDESTRUCTIBLE
- FOR PROFESSIONAL USE
- PROTECTIVE
- MILITARY GRADE
- WITH PRE-CUBED FOAM
- STACKABLE

## RS PRO Flight Cases & Equipment Cases

RS Stock No.: 2537423, 2537424, 2537426, 2537427, 2537428, 2537429, 2537430, 2537431, 2537432, 2537433, 2537434, 2537435, 2537436, 2537437, 2537438, 2537439



**Airtight containers, resistant to chemicals, moisture and dust. Resistant to the most extreme temperatures (-33 ° C / + 90 ° C).**

RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

WATERPROOF CASE IN COPOLYMER POLYPROPYLENE

Indestructible cases recommended for professional use.

REMOVABLE LID WITH SAFETY LOCK

To remove the cover, simply tilt it at 70 ° after releasing the screws on the hinges rear

REINFORCED HINGES WITH ANTI CORROSION METAL PIN

STURDY CLOSURES

SEALING O-RING AND MANUAL PRESSURE RELEASE VALVE

ID REMOVABLE PLATE

ANTI TILT SUPPORTS (in some models)

WITH PRECUBED FOAM INSIDE


SELF OILING FREE RUNNING WHEELS

EASY TO OPEN RELEASE TELESCOPIC HANDLE

TWO MAN LIFT SIDE HANDLES


## General Specifications

METRIC MM-KG-C°



INTERNAL DIMENSIONS		EXTERNAL DIMENSIONS		OTHER DATA	
L LENGTH	765 mm	L LENGTH	860 mm	WEIGHT EMPTY	15.02 Kg
W WIDTH	485 mm	W WIDTH	560 mm	WEIGHT WITH FOAM	18.87 Kg
D DEPTH	415 mm	D DEPTH	460 mm	WEIGHT WITH CUSTOM FOAM	Kg
LID	60 mm			VOLUME	153.90 lt
BASE	355 mm			BUOYANCY	118.50 Kg/max
				OPERATING TEMPERATURE	°C min -33 / max +90

IMPERIAL IN-LBS-F°



INTERNAL DIMENSIONS		EXTERNAL DIMENSIONS		OTHER DATA	
L LENGTH	30 1/8 in	L LENGTH	33 7/8 in	WEIGHT EMPTY	33.11 lbs
W WIDTH	19 1/8 in	W WIDTH	22 1/16 in	WEIGHT WITH FOAM	41.60 lbs
D DEPTH	16 5/16 in	D DEPTH	18 1/8 in	WEIGHT WITH CUSTOM FOAM	lbs
LID	2 3/8 in			VOLUME	40.41 gal
BASE	14 in			BUOYANCY	261.24 lbs/max
				OPERATING TEMPERATURE	°F min -27.4 / max +194