



Main

Range	S-Classic
Product or component type	Bell press switch
Switch application	Bell switch
Quantity per set	Set of 1

Complementary

Control type	Push-button
Actuator	Push-button
Number of gangs	1 gang
Device mounting	Surface Flush
Rated current	10 AX at 250 V AC
Material	Plate: PC (polycarbonate), white Dolly: PC (polycarbonate), white Base: PA66, black
Embedding depth	12.3 mm
Height	87 mm
Width	87 mm
Depth	28.9 mm

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	MS IEC 60669-1 IEC 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.7 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	55 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	14.8 cm
Package 2 Width	18 cm
Package 2 Length	10 cm
Package 2 Weight	622 g
Unit Type of Package 3	CAR
Number of Units in Package 3	100

Package 3 Height	20.3 cm
Package 3 Width	47.3 cm
Package 3 Length	30.5 cm
Package 3 Weight	7430 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations