



REVISIONS			DOC. NO. SPC-F004 * Effective: 7/8/02 * DCP No: 1398					
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1269	Α	RELEASED	JWM	12/2/02	Ю	12/2/02	DJC	12/2/02
1811	В	RoHS ADDED	DCM	12/22/05	JWM	12/22/05	JWM	12/22/05









RoHS

Compliant





Material:

Housing: Thermoplastic Terminal: Copper Alloy

Characteristics:

Rating: 15A 250V AC

Insulation Resistance: Over 100 Ohm 500VDC Dielectric Strength: 2000VAC One Minute

Approvals:

UL, CSA, VDE, SEMKO, DEMKO, NEMKO, SETI, CB and SEV, FIMKO

SPC-F004.DWG

DATE: **TOLERANCES:** DRAWN BY: DRAWING TITLE: AC Power Outlet IEC 320 - C13 12/2/02 Jeff McVicker UNLESS OTHERWISE CHECKED BY: DATE: ELECTRONIC FILE DWG. NO. SPECIFIED, SIZE REV DIMENSIONS ARE 12/2/02 Hisham Odish 2153 В Α 92N4156 FOR REFERENCE APPROVED BY: DATE: PURPOSES ONLY. U.O.M.: INCHES [mm] SCALE: NTS SHEET: OF 1 12/2/02 Daniel Carey

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.