



Portable file belt sanders have replaced tedious hand filing and sanding. First introduced in pneumatic, they are now also available in electric. Increasingly, tool manufacturers are introducing additional fixtures for additional applications. The belts listed are popular stock sizes, but additional sizes, specifications, backing materials, and edge scallops are available made-to-order.

Applications:

Light weld removal and blending, shape and contour sanding, surface preparation prior to coating and plating, removing cutting tool marks from molds and dies, general clean-up

Size Range: Grit Range: Abrasive Grain: Machine Used: 1/8" to 1" wide, 12" to 30" long

40 – 120

Ceramic Alumina, Zirconia Alumina, Aluminum Oxide



Cross Reference Guide

| | BEST | BEST | BETTER | GOOD | GOOD | |
|-----------|---|---------------------------------------|-----------------------------|----------------|---------------------------|--|
| NORTON | Blaze R980P | RedHeat R983 | BlueFire R887D/R823P | Gemini R766 | Gemini R283 | |
| 3M | 963G/H, 966F, 967F, 997F, 984F, 784F, 947A | 747D, 777F, 778F, 784F, 987F, 977F | 577F, 551E | 361F, 363F | 241E, 244E, 251E, 261E | |
| Hermes | CR456 | _ | RB48624YX, RB48644Z | RB377XY, SB378 | RB530J, RB304J, RB306J | |
| Klingspor | CS610 | CS912 | CS411X, CS416, CS409 | CS412, CS413 | CS412 | |
| SIA | 2515, 2503 | _ | 2800,2803, 2815, 2829, 2824 | _ | _ | |
| VSM | XK875X, XK885Y, XK880Y | XK870X, XK870X | ZK713X, ZK713T, KK715X | LK719X, KK711X | KK711E | |
| Sait | _ | _ | AZ-X | 1AX, 2AX | LA-X | |
| Sunmight | _ | _ | _ | P656W | _ | |

Material-to-Product Recommendation Guide

| | BEST | BEST | BETTER | | GOOD | |
|--------------------------|-------------|--------------|----------------|----------------|-------------|-------------|
| | Blaze R980P | RedHeat R983 | BlueFire R887D | BlueFire R823P | Gemini R766 | Gemini R283 |
| Carbon Steel | * | * | * | * | * | * |
| Stainless Steel / Alloys | * | * | * | * | • | |
| Cast Iron | * | * | * | ♦ | * | |
| Brass / Bronze | | | * | * | * | |
| Aluminum | | | * | * | * | |



Best for stainless, cobalt, chrome, inconel, titanium, mild and carbon steel

BLAZE R980P CERAMIC ALUMINA

- Next-generation cooler cutting Norton SG ceramic alumina grain lasts 50% to 200% longer on mild and carbon steel, stainless, cobalt, chrome, inconel and titanium with better metal integrity
- Durable Y-weight polyester, waterproof cloth backing for improved grain adhesion, reduced edge-fray, and better body retention, resulting in longer life and product consistency
- Lubricating grinding aid coating means cooler cut, burn-free grinding of heat-sensitive materials, minimized loading, and improved part finish and integrity



REDHEAT R983 CERAMIC ALUMINA

- Premium ceramic abrasive provides sharp cutting, exceptional life and value, especially on hard-to-grind alloys
- "Supersize" grinding-aid for longer life, cooler cut and minimized loading
- Strong Y-weight polyester, waterproof cloth backing for improved grain adhesion, reduced edge-fray and better body retention, resulting in longer life and product consistency





Better choice for stainless and carbon steel

BLUEFIRE R887D/R823P ZIRCONIA ALUMINA

- Strong, self-sharpening zirconia alumina abrasive for fast, aggressive cut and 30% longer life than competitive zirconia belts
- · Durable resin bond for excellent grain retention and product life
- Strong Y-weight polyester backing R887D for heavy-duty stock removal applications; flexible X-weight polyester backing - R823P for moderate- to light-pressure applications



Good choice for difficult-to-grind materials (aluminum, brass, bronze, stainless, carbon steel, titanium, etc.)

GFMINI R766 ALUMINUM OXIDE

- Premium aluminum oxide abrasive blend is ideal when primary purchasing criteria is a good-performing, economically-priced, general-purpose belt
- Y-weight waterproof polyester backing withstands light- to moderately-demanding applications and provides extended life on dry grinding applications
- · Resin bond system provides improved edge retention and 30% plus improvement in life versus key competitors



Good choice for stainless and carbon steel applications when initial price is the primary purchasing factor $\,$

GEMINI R283 ALUMINUM OXIDE

- P-graded premium aluminum oxide abrasive for consistent, cool cut
- Strong, semi-flexible, smooth X-weight rayon waterproof backing is designed for light- to moderate- pressure applications
- · Durable resin coating provides excellent grain retention and product life



BLUEFIRE R887D/R823P

GEMINI R766

GEMINI R283

| | | ABRASIVE: | Ceramic Alumina | Ceramic Alumina | Zirconia Alumina | Aluminum Oxide Blend | Aluminum Oxide |
|--------------|------|-----------|------------------------|------------------------|--------------------------|------------------------|---------------------|
| | | BACKING: | Y-Weight Polyester | Y-Weight Polyester | Y- or X-Weight Polyester | Y-Weight Polyester | X-Weight Rayon |
| | | OTHER: | Supersize | Supersize | | • | |
| SIZE (W x L) | GRIT | STD. PKG. | PART # | PART # | PART # | PART # | PART # |
| 12" Belts | | | | | | | |
| 1/8 x 12 | 40 | 50 | | | | 666233 90000 NS | |
| | 60 | 50 | 662544 05345 NS | | 662610 93029 NS | | |
| | 80 | 50 | | 662544 91523 NS | | | |
| | 120 | 50 | | 662544 91524 NS | | | |
| 1/4 x 12 | 40 | 50 | 662544 91520 NS | | | | |
| | 60 | 50 | 662611 96480 NS | | 780727 58896 | | |
| | 80 | 50 | | 662544 91526 NS | 780727 82621 | | 780727 66143 |
| | 120 | 50 | 662610 63632 NS | | 780727 82622 | | 780727 63175 |
| 1/2 x 12 | 40 | 50 | 699573 98018 | 662544 91528 NS | 662544 92522 | 666233 90006 | 780727 27557 |
| | 50 | 50 | 662610 43759 | 780727 18700 | | | |
| | 60 | 50 | 699573 98019 | 780727 18701 | 780727 28745 | 666233 90008 NS | 780727 27555 |
| | 60 | 25 V | | | 666233 73753 | | |
| | 80 | 50 | 699573 98020 | 780727 18702 | 780727 28744 | 666233 90009 | 780727 27554 |
| | 80 | 25 V | | | 666233 73754 | | |
| | 100 | 50 | 662610 81180 | | 662544 91534 | | 780727 27553 |
| | 120 | 50 | 662610 42909 | 780727 00518 NS | 780727 28742 | | 780727 27552 |
| 1 x 12 | 60 | 50 | 662610 63641 NS | | 780727 53073 | | 780727 73813 |

Additional sizes, grits and scalloped edge belts are available MTO (made-to-order). Contact your Norton representative for availability, order quantities and lead-times.

REDHEAT R983

40 and 50 grit BlueFire belts are furnished in BlueFire R887D (Y-weight Polyester); 60-120 grits are supplied in BlueFire R823P (X-weight Polyester).

Joints — All belts are PG jointed; a butt joint joined with flexible tape for contour grinding.

TRADENAME: BLAZE R980P

V = Vendible package. Ideal for vending machines and small jobs. 5 belts per pack / 5 packs per carton. Order in multiples of 25.

NS Non-Stock, contact your Norton representative for current order quantities and lead times.

continued