



## Overview

Lead time	Usually in Stock
-----------	------------------

## Main

Colour	Black
PDU type	Switched
Cable length	3.00 m
Number of cables	1
Provided equipment	Installation guide Locking input power cord Rack mounting brackets Safety guide

## Complementary

Main Input Voltage	230 V
Height	179.4 cm
Width	5.5 cm
Main Output Voltage	230 V
Depth	4.6 cm
Net weight	5.61 kg
Mounting location	Side
Mounting preference	No preference
Input Connection Type	IEC 60309 16 A 2P + E IEC 60320 C20
Mounting mode	Not rack-mountable
Number of rack unit	0U
USB compatible	No
Mounting position	Vertical
Communication port protocol	SNMP Redfish
Permissible voltage	220...240 V
Max line current	16 A
Input current limits	16 A
Load capacity	3700 VA
Network frequency	50/60 Hz
Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
Communication network type	10/100/1000BASE-T

## Environment

Product certifications	FCC part 15 class A[RETURN]VDE[RETURN]RCM[RETURN]EAC
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 ICES-003
Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	200.2 cm
Package 1 Width	11.4 cm
Package 1 Length	16.5 cm
Package 1 Weight	8.59 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------