

# AP6003A

## RACK PDU, BASIC, HALF HEIGHT, 100-240V/20A, 220-240V/16A, (14) C13



### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Colour	Black
PDU type	Basic
Provided equipment	Installation guide Safety guide

### Complementary

Main Input Voltage	230 V
Height	52.3 cm
Width	5.6 cm
Main Output Voltage	100 V 120 V 200 V 208 V 230 V 240 V
Depth	4.7 cm
Net weight	1.88 kg
Mounting location	Side
Mounting preference	Lower
Input Connection Type	IEC 60320 C20
Mounting mode	Not rack-mountable
Number of rack unit	0U
USB compatible	No
Mounting position	Vertical
[In] rated current	16 A
Permissible voltage	100...240 V
Max line current	20 A
Input current limits	20 A
Load capacity	3300 VA
Network frequency	50/60 Hz
Number of power socket outlets	14 IEC 60320 C13

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Product certifications	cUL listed[RETURN]UL listed
Ambient air temperature for operation	0...50 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	61.2 cm
Package 1 Width	10.7 cm
Package 1 Length	12.3 cm
Package 1 Weight	2.55 kg
SCC14	10731304327766

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------