VW3A1101

remote graphic terminal, Altivar, 240 x 160pixels, IP54





Main

Altivar
Altivar 312 Altivar 61 Altivar Lift Altivar 32 Altivar Machine ATV320 Altivar 312 Solar Altivar 212 Altivar 71 Altivar 61Q Altivar 71Q
Display and signalling accessories
Display terminal
Variable speed drive
To control, adjust and configure the drive To save and download configurations To display the current values
IP54

Complementary

Mounting location	On the door of an enclosure	
Language	Italian	
	English	
	French	
	Spanish	
	German	
	Chinese	
Messages display capacity	8 lines	
Pixel resolution	240 x 160	
Net weight	0.145 kg	

Environment

Ambient air temperature for operation	-15 50 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.000 cm
Package 1 Width	16.500 cm
Package 1 Length	23.000 cm
Package 1 Weight	275.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	2.413 kg
Unit Type of Package 3	P06
- The Type of Fackage 5	1 00

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Number of Units in Package 3	56
Package 3 Height	77.000 cm
Package 3 Width	80.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	28.420 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty 18	B months
-------------	----------