

## FEATURES

- Robust design
- Durable tin plated steel shell
- Dimples on the shell (plugs only) for improved electrical conductivity and grounding
- Reliable gold plated machined contacts
- Flanges with for mounting holes for screw mounting to a panel
- Solder cup terminations for simple wire connection

## RS PRO 25 Way Panel Mount D-sub Connector Plug, 2.77mm Pitch

RS Stock No.: 544-3812



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

From RS PRO a durable D-Subminiature connector with a robust steel shell, reliable machined contacts and solder cup terminations that allow the easy connection of wires. These D-sub connectors are ideal for use for making I/O (input/output) interconnections in a wide range of industrial and commercial applications.

## General Specifications

<b>Number Of Contacts</b>	25
<b>Gender</b>	Male
<b>Body Orientation</b>	Straight
<b>Mounting Type</b>	Panel Mount
<b>D Connector</b>	Standard D-Sub
<b>Termination Method</b>	Solder
<b>Housing Material</b>	Steel
<b>Dimensions</b>	53.04mm x 10.82mm x 12.55mm
<b>Contact Material</b>	Copper Alloy
<b>Contact Plating</b>	Gold
<b>Application</b>	Computers, monitors and scanners, Networking and communications equipment; Data processing equipment, Industrial equipment, Test and measurement instrumentation, Remote Sensors and data loggers, Portable electric generation equipment
<b>Durability</b>	150 Mating Cycles

## Electrical Specifications

<b>Current Rating</b>	5.0A
<b>Voltage Rating</b>	500V
<b>Contact Resistance</b>	10m ohm MAX

**Mechanical Specifications**

<b>Pitch</b>	2.77mm
<b>Length</b>	53.04mm
<b>Width</b>	10.82mm
<b>Depth</b>	12.55mm

**Operation Environment Specifications**

<b>Maximum Operating Temperature</b>	+105°C
<b>Minimum Operating Temperature</b>	-55°C

**Approvals**

<b>Compliance/Certifications</b>	D / 2011/65/EU and 2015/863
----------------------------------	-----------------------------



