

## In-Line 60A Twistlock male and female connectors

### Product Code: GHT9002

**Product:** 60A Male brass twistlock connector

**Application:** Replacement 60A, male, twistlock, brass connector for ceramic heating elements.



### Product Code: GHT9001

**Product:** 60A Male twistlock connector complete set.

**Application:** Replacement 60A, male, twistlock, connector for ceramic heating elements.



### Product Code: GHT9003

**Product:** 60A Male twistlock connector sleeve.

**Application:** Replacement 60A, male, twistlock, connector sleeve for ceramic heating elements.



### Product Code: GHT9004

**Product:** 60A Male twistlock connector higher temp sleeve.

**Application:** Higher temperature replacement 60A, male, twistlock, connector sleeve for ceramic heating elements.



### Product Code: GHT9005

**Product:** 60A Female twistlock connector complete set.

**Application:** Replacement 60A, female, twistlock, connector for splitter cables.



### Product Code: GHT9006

**Product:** 60A Female brass twistlock connector

**Application:** Replacement 60A, female, twistlock, brass connector for splitter cables.



### Product Code: GHT9007

**Product:** 60A Female twistlock connector sleeve.

**Application:** Replacement 60A, female, twistlock, connector sleeve for splitter cables.



### Product Code: GHT9008

**Product:** 60A Female twistlock connector higher temp sleeve.

**Application:** Higher temperature replacement 60A, female, twistlock, connector sleeve for splitter cables.



### Product Code: GHT9009

**Product:** 60A pin

**Application:** For fixing 60A male and female connector sleeves to 60A brass connectors.



Specification			
<b>Standard Sleeves</b>		<b>Brass Connectors</b>	
Material	Insulated Paper	Material	Brass (Hpb59-1)
Density	0.45g/cm <sup>3</sup>	Current	60A
Water Absorption	0.30%	Dielectric strength	20KV/mm
Compressive Strength	36.5 MPa	Working Temperature	-20°C to +100°C
Working Temperature	-20°C to +110°C	<b>Brass (Hpb59-1) % components:-</b>	
<b>Higher Temperature Sleeves</b>		• Cu	59%
Material	Epoxy	• Hpb59-1Ni	1%
Density	1.90g/cm <sup>3</sup>	• Fe	0.5%
Water Absorption	0.10%	• Pb	1.5%
Compressive Strength	104.6 MPa	• Zn	37%
Working Temperature	-20°C to +140°C	• Others	1%