



ENGLISH

Datasheet

Stock No: 811-4359

RS Pro 3 Core White Unscreened 2183Y Solid PVC Power Cable H03VV-F, 0.75 mm² CSA 6 A, 300 V



Image representative of range

Product Details

BASEC approved H03VV-F/2183Y 3 Core Cable

2183Y 3 core cable can be used with household applications in covered, dry, steamed and humid areas where low mechanical stress exists

Features and Benefits

- Flexible, 3 core cable with fine stranded copper conductors
- PVC sheath
- PVC insulation

Standards

BASEC

Flexible PVC Cable

Specifications:

Number of Cores	3
Cross Sectional Area	0.75 mm ²
Sheath Colour	White
Current Rating	6 A
Voltage Rating	300 V
Outer Diameter	6.7mm
Sheath Material	Polyvinyl Chloride PVC
Harmonised Code	H03VV-F
Type	2183Y
Minimum Operating Temperature	-15°C
Maximum Operating Temperature	+70°C
Screened/Unscreened	Unscreened
Conductor Strand Type	Solid
Conductor Resistance	26 Ω/km
Size of Strands	0.2 mm
Core Strands	24/0.2 mm
Number of Strands	24
Insulation Material	PVC
Conductor Material	Copper
American Wire Gauge	18 AWG