



### Main

Range	Pieno
Product or component type	Connection unit
Rated current	45 A at 250 V AC 50 Hz
Load type	Resistive
Protection type	Fuse
Number of gangs	1 gang
Cover frame colour tint	White

### Complementary

Wiring device mounting	Surface Flush
Material	Polycarbonate: surround Polycarbonate: grid plate
Clamping connection capacity	3 x 4 mm <sup>2</sup> for stranded cable(s) 1 x 10 mm <sup>2</sup> for solid cable(s)
Connections - terminals	Pillar terminals
Width	87 mm
Height	87 mm
Depth	43.82 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Standards	BS 5733

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.382 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	147.05 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	882.3 g
Unit Type of Package 3	CAR
Number of Units in Package 3	60
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	10250.1 g

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------