

SPECIFICATIONS

MODEL		CWG-30375		CWG-30565		CWG-30750		CWG-31500		CWG-34000	
Option		A	B	A	B	A	B	A	B	A	B
Lifting capacity kg wire rope top layer		900		1,100		2,200		3,500		5,000	
Lifting speed, m/min	first layer	13	8.5	14	9.2	6.9	4.5	5.8	4.4	8	5.3
	top layer	20.6	13.5	25	16.4	12.6	8.3	8	6	12.2	8
Motor rating IP54	type	Induction		Induction		Induction		Induction		Induction	
	output, kw x poles	3.8 x 4	2.2 x 6	5.5 x 4	3.8 x 6	5.5 x 4	3.8 x 6	5.5 x 6	3.8 x 8	11 x 4	7.5 x 6
Gear ratio		48:1		50:1		127:1		192:1		197:1	
Maximum lifting height, m		58		97		97		144		192	
Braking methods		Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic		Electromagnetic	
Wire rope	size, mm x m	*10 x 60		*12 x 100		*16 x 100		*18 x 150		*22.4 x 200	
	construction	6 x 24		6 x 24		6 x 24		6 x 24		6 x 24	
	breaking strength, kg	4,640		6,680		11,900		15,000		23,300	
Drum dimension, mm	length	230		312		312		405		680	
	drum dia.	127		140		178		356		324	
	flange dia.	275		320		410		570		570	
Mounting bolts pattern (mm x mm)		500 x 370		620 x 425		600 x 499		847 x 680		920 x 680	
Net weight, kg (standard version)		185		250		400		800		1,380	
Gross weight, kg		225		285		445		870		1,545	
Body dimension, mm (L x D x H)		974 x 400 x 445		1,120 x 470 x 520		1,246 x 565 x 658		1,439 x 740 x 860		1,860 x 740 x 905	
Box dimension, mm (L x D x H)		1,140 x 590 x 620		1,290 x 650 x 680		1,390 x 710 x 830		1,590 x 840 x 1,020		2,040 x 840 x 1,100	