



Main

| | |
|---------------------------|-------------------------------------|
| Range of product | AvatarOn C |
| Product or component type | Switched socket |
| Device application | Power supply |
| Device presentation | Basic element with complete housing |
| Colour tint | White |

Complementary

| | |
|--------------------------------|--------------------|
| Rated current | 13 A socket-outlet |
| [Ue] rated operational voltage | 250 V AC 50/60 Hz |
| Socket number | 2 |
| Outlet standard | British |
| Number of gangs | 2 gangs |
| Pilot light | LED |
| Material | PC (polycarbonate) |
| Device mounting | Surface |
| Fixing mode | By screws |
| Height | 86 mm |
| Width | 146 mm |
| Depth | 30.8 mm |

Environment

| | |
|-------------------------|------|
| IP degree of protection | IP20 |
|-------------------------|------|

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.1 cm |
| Package 1 Width | 14.6 cm |
| Package 1 Length | 8.6 cm |
| Package 1 Weight | 134.0 g |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Green Premium product |
| RECh Regulation | RECh Declaration |
| RECh free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |

RoHS exemption information

 [Yes](#)

Environmental Disclosure

 [Product Environmental Profile](#)
