CCT570003
ARGUS Standard 360° False ceiling indoor movement detector - 2ch

Green Premium™

Main

Range of product	ARGUS standard movement detector
Range	ARGUS
Product or component type	Movement detector
Load type	LED lighting: : 100 W Compact fluorescent lamp: : 100 W Motor: : 100 W Relay: : 5 A - 250 V Incandescent lamps: : 1000 W - 230 V Halogen lamp: : 900 W - 230 V Halogen lamp with standard electronic transformer: 250 VA Halogen lamp with standard ferromagnetic transformer: 500 VA Fluorescent tube: 200 VA Capacitive: , 21 µF Capacitive: , 14 µF
Colour tint	White

Complementary

Output voltage	220...250 V
Control type	Movement sensor
Function available	Switching, toggling, dimming
Light intensity adjustment	5…1000 lux
Detection range	Radius: 3500 mm
Device mounting	Ceiling Flush
Mounting height	2.5 m

Environment

IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	12.6 cm
Package 1 Length	13.0 cm
Package 1 Weight	265.0 g
Unit Type of Package 2	S04
Number of Units in Package 2	48
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	13.56 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins