

FEATURES

- Threaded hollow cavity inserts
- M4 threading
- Suitable for material thickness range of 0.38 mm to 4.75 mm
- Fixing hole diameter 8.38 mm
- Flange diameter 11.89 mm
- Outer body diameter 8.08 mm
- Body depth 16.59 mm
- Bright zinc-plated mild steel construction for corrosion resistance

RS PRO Bright Zinc Plated, M4 Steel Threaded Insert, 11.89mm diameter 8.38mm Depth 16.59mm

RS Stock No.: 768-0729



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

This RS PRO threaded insert is a simple way to make threaded holes in sheet materials for screws, bolts or other fixings. Place the insert and a screw into any hole of the provided friction wrench, push the assembly through the pre-drilled hole, hold the wrench firmly and tighten the screw till it sits snugly in the sheet.

General Specifications

Thread Size	M4
Material	Steel
Finish	Bright Zinc Plated
Application	Maintenance of domestic electronics like refrigerators

Mechanical Specifications

Flange Diameter	11.89mm
Fixing Hole Diameter	8.38mm
Body Outside Diameter	8.08mm
Body Depth	16.59mm
Thickness Of Material Maximum	4.75mm
Thickness Of Material Minimum	0.38mm

Approvals

Compliance/Certifications	EN61340
----------------------------------	---------

