

# 8562 C - 8567 CL

## TORQUE WRENCH DREMOMETER

60-300 N·m / 45-220 lbf·ft

### Use:

- › Controlled screw tightening in the range 60-300 N·m / 45-220 lbf·ft
- › For use in almost all industrial manufacturing areas

### Features:

- › Classified to DIN EN ISO 6789:2003 Type II Class A, with a factory certificate. Working accuracy:  $\pm 3\%$  tolerance of scale set torque. The specification of the standard ( $\pm 4\%$ ) is exceeded.
- › 1/2" square drive with ball locking device DIN 3120 - A 12.5, ISO 1174
- › Automatic short-path actuation with tactile impulse and audible signal
- › Dual scale with a scale graduation of 5 N·m and 5 lbf·ft
- › **With push-button release**

### Technical advantage/Function:


- › Lightweight and robust (as housing is made of an aluminium alloy), very workshop-friendly
- › No inaccuracies whether used with both hands or held away from the handle (as for standard torque wrenches). Both the square drive and fulcrum are on an axis which ensures a high degree of user safety; can be extended to reduce the user's working load.
- › Extremely low wear attributable to reduced forces in a unique lever mechanism
- › Forged lever chain from our own quality forge
- › Maximum precision even when subjected to extreme continuous use
- › Long life cycles and tool lives
- › Easy operation - fast and safe torque tightening
- › Easy adjustment thanks to attractive adjusting button secured against loss at the end of the handle
- › Single- and double-square drive for controlled bi-directional tightening



8562-30



CR



| Type | □   | ■    | Contents   | N·m    | lbf·ft | lw  | a  | b    | c   | Tube     | Scale            | Weight | Code    | No.      |
|------|-----|------|--|--------|--------|-----|----|------|-----|----------|------------------|--------|---------|----------|
| CR   | 1/2 | 12.5 | in plastic box with ALU extension tube   | 60-300 | 45-220 | 529 | 30 | 17.5 | 617 | 8577-700 | 5 N·m / 5 lbf·ft | 2.7    | 2926997 | 8562-001 |
| C    | 1/2 | 12.5 | in plastic box   | 60-300 | 45-220 | 529 | 30 | 17.5 | 617 | —        | 5 N·m / 5 lbf·ft | 2.0    | 7685450 | 8562-10  |
| C    | 1/2 | 12.5 | in a sheet-metal case  | 60-300 | 45-220 | 529 | 30 | 17.5 | 617 | —        | 5 N·m / 5 lbf·ft | 3.6    | 7686340 | 8562-20  |
| C    | 1/2 | 12.5 | Set mm<br>○ 17 19 22 24 27 30 32<br>● 8 10 12 14<br>754-02 76 + 125 + 250 mm   | 60-300 | 45-220 | 529 | 30 | 17.5 | 617 | —        | 5 N·m / 5 lbf·ft | 6.0    | 7687070 | 8562-30  |
| C    | 1/2 | 12.5 | Set INCH<br>○ 3/4 25/32 13/16 7/8 15/16 1"<br>1.1/16 1.1/8 1.1/4"<br>● 3/8 1/2 9/16 5/8"<br>754-02 76 + 125 + 250 mm | 60-300 | 45-220 | 529 | 30 | 17.5 | 617 | —        | 5 N·m / 5 lbf·ft | 6.2    | 7687820 | 8562-40  |
| CL   | 1/2 | 12.5 | in plastic box   | 60-300 | 45-220 | 529 | 30 | 17.5 | 617 | —        | 5 N·m / 5 lbf·ft | 2.0    | 7685960 | 8567-10  |
| CL   | 1/2 | 12.5 | in a sheet-metal case  | 60-300 | 45-220 | 529 | 30 | 17.5 | 617 | —        | 5 N·m / 5 lbf·ft | 3.6    | 7686690 | 8567-20  |
| CL   | 1/2 | 12.5 | Set mm<br>○ 17 19 22 24 27 30 32<br>● 8 10 12 14<br>754-02 76 + 125 + 250 mm   | 60-300 | 45-220 | 529 | 30 | 17.5 | 617 | —        | 5 N·m / 5 lbf·ft | 6.0    | 7687310 | 8567-30  |
| CL   | 1/2 | 12.5 | Set INCH<br>○ 3/4 25/32 13/16 7/8 15/16 1"<br>1.1/16 1.1/8 1.1/4"<br>● 3/8 1/2 9/16 5/8"<br>754-02 76 + 125 + 250 mm | 60-300 | 45-220 | 529 | 30 | 17.5 | 617 | —        | 5 N·m / 5 lbf·ft | 6.2    | 7688120 | 8567-40  |