



Instruction Data sheet

ENGLISH

COOLING CONTROLLER

Stock Number: 2228130



77 x 35 DIN Size Digital , ON / OFF Cooling Controller

- 4 Digits Display
- NTC Input
- 3 output for compressor, defrost and fan controls
- 2 sensor input for cabinet and evaporator
- Configurable digital input
- ON / OFF Control
- Separately adjustable 2 offset value for cabinet and evaporator sensor
- Set value boundaries
- Operation selection of compressor operate continuously, stops or operates periodically in case of cabinet probe defect
- Compressor protection delays
- Selectable defrost function (hot gas or electric)
- Adjustable defrost time from front panel
- Manual defrost from front panel
- Defrost parameters
- Alarm parameters
- Fan can be operated depending on compressor and defrost
- Fan can be operated depending on evaporator temperature or (cabinet - evaporator) temperature
- Adjustable internal buzzer according to the defrost, cabinet prob defect and alarm status
- Defrost time and/or manual defrost and/or temperature set value protection
- Password protection for programming mode
- Installing parameters using Prokey
- Remote access, data collecting and controlling with Modbus RTU
- Having CE mark according to European Norms





ENGLISH

Specifications

Input

Temperature Sensor Inputs: NTC
NTC Input Type (10 kΩ @25 °C)

Output

Relay Outputs : 16(8) A@250 V ~ at resistive load(Compressor Output)
: 5 A@250 V ~ at resistive load(Defrost and Fan Output)

Environmental Rating and Physical Specification

Storage / Operating Temperature : -40 °C to +85 °C / 0 °C to +50 °C
Storage / Operating Humidity : 90 % max. (None condensing)
Protection Class : NEMA 4X (IP65 at front, IP20 at rear)

Supply Voltage

230Vac (-%15, +%10) 50/60Hz

Dimensions

77x35mm

Electrical Wirings

