


**Datasheet**

# RS PRO DC Motor, 7 W, 4.5 - 15 V, 6000 gcm, 9 rpm, 6mm Shaft Diameter

Stock No: 752-1992

**Specifications:**

Output Speed	9 rpm
Supply Voltage	4.5 - 15 V dc
Maximum Output Torque	6000 g.cm
DC Motor Type	Brushed
Shaft Diameter	6mm
Power Rating	7 W
Gearhead Type	Spur
Length	75.9mm
Width	37mm
Current Rating	840 mA
Weight	220g



Operating relative humidity 20% ~ 85%  
 Operating temperature range -10°C ~ +60°C

Ratio	L
810:1	29.5mm

Gearbox Housing material	Metal
Backlash at no-load	< 2°
Bearing at output	Sleeve bearings
Radial load (10mm from flange)	< 1 kgf
Shaft axial load	< 0.7 kgf
Shaft press fit force max	< 20 kgf
Radial play of shaft	< 0.05mm
Thrust play of shaft	< 0.35mm

Reduction Ratio	Rated tolerance Torque	Max momentary Tolerance Torque	Efficiency
1/900	6 kgf-cm Max.	18 kgf-cm	53%

Reduction Table RPM	4.5v	6v	9v	12v	15v
SUPPLY VOLTAGE					
752-1992	3	4.5	7	9	11

Note: Motor speeds may vary by (+) or (-) 10%