

APDU9981EU3

APC Rack PDU 9000 Switched, ZeroU,
11.0kW, 230V, (21) C13 & (3) C19



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Colour	Black
PDU type	Switched
Cable length	1.83 m
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets Safety guide

Complementary

Main Input Voltage	400 V 3 phases
Height	179.2 cm
Width	5.5 cm
Main Output Voltage	230 V
Depth	4.6 cm
Net weight	7 kg
Mounting location	Side
Mounting preference	No preference
Input Connection Type	IEC 60309 16 A 3P + N + PE
Mounting mode	Not rack-mountable
Number of rack unit	0U
USB compatible	No
Mounting position	Vertical
Communication port protocol	SNMP Redfish
[In] rated current	16 A
Max line current	16 A
Input current limits	16 A
Load capacity	11000 VA
Network frequency	50/60 Hz
Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19
Communication network type	10/100/1000BASE-T

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Product certifications	cUL listed[RETURN]FCC part 15 class A[RETURN]UL listed[RETURN]VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 ICES-003
Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	200.2 cm
Package 1 Width	11.4 cm
Package 1 Length	16.5 cm
Package 1 Weight	8.95 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------