

Wire Wound Chip Inductor Ferrite

multicomp PRO

**RoHS
Compliant**




Features:

- Very strong solderability by flow soldering, soldering iron or wave soldering
- Highly accurate dimensions, can be mounted automatically
- Terminals are highly resistant to pull forces
- Highly resistant to mechanical shocks and pressure
- Highly reliable in environments of sudden temperature change and humidity. Super Q characteristics


Applications:

Micro Televisions, Liquid Crystal Televisions, Video Cameras, Portable VCRs, Car Radios, Car Stereos, Thin Tape Radios, Television Tuners, Mobile Telephones, Radio and Other Electronic Devices

Construction:



1. Molded resin
2. Electrode (Tinned Copper Wire)
3. Ferrite core
4. Magnet wire



1. Ferrite core
2. Magnet wire
3. Electrode (Ag/Pd+Ni+Sn)
4. UV Glue

Dimensions:




Figure 1

Figure 2

Figure 3

Size (In)	Fig.	A	B	C	D	E	F	G	H	I	J	K	Weight (g) (1000pcs)
0805	1	2.4 max	1.71 max	1.45 max	0.65	-	0.44	1.02	1.78	1.02	0.76	1.27	14
1008	1	2.92 max	2.79 max	2.1 max	1.2	-	0.45	1.52	2.54	1.02	1.27	2.03	30
1210	2	3.2±0.4	2.5±0.2	2.2 ±0.2	1±0.2	0.6 -0/+0.3	-	-	1.4	1	1.8	-	40
1812	2	4.5±0.3	3.2±0.2	3.2 ±0.2	1.2	1 -0/+0.3	-	-	1.6	1.5	2.2	-	160

Dimensions : Millimetres

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO


Wire Wound Chip Inductor Ferrite

Colour Coding:

0805 / 1008 Type

Because of small sizes, these parts are marked with a single colour dot.

The inductance value represented by the dot is shown on the data page for each type.



Standard Electrical Specifications:

0805 Wire Wound Chip Inductors (Ferrite / Open Type) / Standard Type

Part Number	Inductance (µH)	Tolerance	Q min.	Test Freq. (MHz)	SRF (MHz) min.	DCR (Ω) max.	IDC (mA) max.	Colour Code
MCFT000152	0.15	±5, ±10%	20	25.2	900	0.18	1100	Gray
MCFT000153	0.22	±5, ±10%	20	25.2	550	0.25	700	Brown
MCFT000154	0.33	±5, ±10%	20	25.2	550	0.35	650	Orange
MCFT000155	0.47	±5, ±10%	20	25.2	350	0.45	600	Green
MCFT000156	0.68	±5, ±10%	20	25.2	300	0.6	500	Violet
MCFT000157	1	±5, ±10%	15	7.96	280	0.8	450	White
MCFT000158	1.5	±5, ±10%	15	7.96	250	1.05	350	Brown
MCFT000159	2.2	±5, ±10%	15	7.96	110	1.1	320	Orange
MCFT000160	3.3	±5, ±10%	15	7.96	60	1.5	300	Green
MCFT000161	4.7	±5, ±10%	15	7.96	45	2.1	200	Violet
MCFT000162	6.8	±5, ±10%	15	7.96	36	2.7	200	White
MCFT000163	10	±5, ±10%	10	2.52	30	4.5	180	Brown

Standard Electrical Specifications:

1008 Wire Wound Chip Inductors (Ferrite / Open Type) / Standard Type

Part Number	Inductance (µH)	Tolerance	Q min.	Test Freq. (MHz)	SRF (MHz) min.	DCR (Ω) max.	IDC (mA) max.	Colour Code		
MCFT000165	0.22	±5, ±10%	27	25.2	600	0.4	880	Red	Red	Brown
MCFT000166	0.33	±5, ±10%	30	25.2	400	0.42	900	Orange	Orange	Brown
MCFT000167	0.47	±5, ±10%	30	25.2	350	0.5	900	Yellow	Violet	Brown

Wire Wound Chip Inductor Ferrite

multicomp PRO

Part Number	Inductance (µH)	Tolerance	Q min.	Test Freq. (MHz)	SRF (MHz) min.	DCR (Ω) max.	IDC (mA) max.	Colour Code		
MCFT000168	0.68	±5, ±10%	30	25.2	300	0.55	800	Blue	Gray	Brown
MCFT000169	1	±5, ±10%	25	7.96	245	0.6	600	Brown	Black	Red
MCFT000170	1.5	±5, ±10%	25	7.96	182	0.85	550	Brown	Green	Red
MCFT000171	2.2	±5, ±10%	25	7.96	105	1.1	500	Red	Red	Red
MCFT000172	3.3	±5, ±10%	25	7.96	55	1.37	350	Orange	Orange	Red
MCFT000173	4.7	±5, ±10%	25	7.96	43	1.68	300	Yellow	Violet	Red
MCFT000174	6.8	±5, ±10%	25	7.96	39	1.85	300	Blue	Gray	Red
MCFT000175	10	±5, ±10%	20	2.52	33	2.32	250	Brown	Black	Orange
MCFT000176	15	±5, ±10%	15	2.52	24	3.42	200	Brown	Green	Orange
MCFT000177	22	±5, ±10%	15	2.52	18	5.12	180	Red	Red	Orange
MCFT000178	33	±5, ±10%	15	2.52	16	6.44	120	Orange	Orange	Orange
MCFT000179	47	±5, ±10%	14	2.52	13	9.94	110	Yellow	Violet	Orange
MCFT000180	68	±5, ±10%	14	2.52	8	12.8	90	Blue	Gray	Orange
MCFT000181	100	±5, ±10%	8	1	7	19.6	120	Brown	Black	Yellow

Standard Electrical Specifications:

1210 Wire Wound Chip Inductors (Ferrite / Open Type) / Standard Type

Part Number	Inductance (µH)	Tolerance	Q min.	Test Freq. (MHz)	SRF (MHz) min.	DCR (Ω) max.	IDC (mA) max.
MCFT000182	1	±10%	30	7.96	120	0.7	400
MCFT000183	1.5	±10%	30	7.96	85	0.85	370
MCFT000184	2.2	±10%	30	7.96	75	1	320
MCFT000185	3.3	±10%	30	7.96	60	1.2	260
MCFT000186	4.7	±10%	30	7.96	50	1.5	220
MCFT000187	6.8	±10%	30	7.96	40	1.8	180
MCFT000187	10	±10%	30	2.52	30	2.1	150
MCFT000189	15	±10%	30	2.52	20	2.8	130
MCFT000190	22	±10%	30	2.52	20	3.7	110
MCFT000191	33	±10%	30	2.52	17	5.6	70
MCFT000191	47	±10%	30	2.52	15	7	60
MCFT000193	68	±10%	30	2.52	12	9	50
MCFT000194	100	±10%	20	0.796	10	10	40
MCFT000195	150	±10%	20	0.796	8	15	65

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO

Wire Wound Chip Inductor Ferrite

multicomp PRO

Standard Electrical Specifications:

1812 Wire Wound Chip Inductors (Ferrite / Open Type) / Standard Type

Part Number	Inductance (μH)	Tolerance	Q min.	Test Freq. (MHz)	SRF (MHz) min.	DCR (Ω) max.	IDC (mA) max.
MCFT000197	1	±10%	50	7.96	100	0.5	450
MCFT000198	1.5	±10%	50	7.96	70	0.6	410
MCFT000199	2.2	±10%	50	7.96	55	0.7	380
MCFT000200	3.3	±10%	50	7.96	45	0.8	355
MCFT000201	4.7	±10%	50	7.96	35	1	315
MCFT000202	6.8	±10%	50	7.96	27	1.2	285
MCFT000203	10	±10%	50	2.52	20	1.6	250
MCFT000204	15	±10%	50	2.52	17	2.5	200
MCFT000205	22	±10%	50	2.52	13	3.2	180
MCFT000206	33	±10%	50	2.52	11	4	160
MCFT000207	47	±10%	50	2.52	10	5	140
MCFT000208	68	±10%	50	2.52	9	6	130
MCFT000209	100	±10%	40	0.796	8	8	110
MCFT000210	150	±10%	40	0.796	5	9	105
MCFT000211	220	±10%	40	0.796	4	10	100
MCFT000212	330	±10%	30	0.796	3.5	15	85
MCFT000213	470	±10%	30	0.796	3	26	62
MCFT000214	680	±10%	30	0.796	3	30	50

Low Profile Electrical Specifications:

0805 Wound Chip Inductors (Ferrite / Open Type) / Low Profile Type

Part Number	Inductance (μH)	Tolerance	Q min.	Test Freq. (MHz)	SRF (MHz) min.	DCR (Ω) max.	IDC (mA) max.
MCFT000157	1	±5, ±10%	15	L: 7.96 / Q: 25.2	115	0.9	450
MCFT000160	3.3	±5, ±10%	13	7.96	70	1.4	450
MCFT000161	4.7	±5, ±10%	15	7.96	65	1.9	400
MCFT000162	6.8	±5, ±10%	15	7.96	41	2.4	400
MCFT000163	10	±5, ±10%	14	7.96	31	2.7	400

Wire Wound Chip Inductor Ferrite

multicomp PRO

Large Current Electrical Specifications:

0805 Wound Chip Inductors (Ferrite / Open Type) / Large Current Type

Part Number	Inductance (µH)	Tolerance	Q typ.	Test Freq. (MHz)	SRF (MHz) typ.	DCR (Ω) max.	IDC (mA) max.	Colour Code
MCFT000155	0.47	±10, ±20%	14	25.2	850	0.156	1,400	Blue
MCFT000156	0.68	±10, ±20%	14	25.2	765	0.195	1,200	Gray
MCFT000157	1	±10, ±20%	14	7.96	208	0.169	1,100	Black
MCFT000158	1.5	±10, ±20%	14	7.96	159	0.221	920	Brown
MCFT000159	2.2	±10, ±20%	13	7.96	87	0.286	740	Red
MCFT000160	3.3	±10, ±20%	12	7.96	70	0.364	620	Orange
MCFT000161	4.7	±10, ±20%	14	7.96	51	0.559	520	Yellow
MCFT000162	6.8	±10, ±20%	14	7.96	46	0.884	420	Green
MCFT000163	10	±5, ±10, ±20%	14	2.52	31	1.105	360	Blue

Large Current Electrical Specifications:

1008 Wound Chip Inductors (Ferrite / Open Type) / Large Current Type

Part Number	Inductance (µH)	Tolerance	Q typ.	Test Freq. (MHz)	SRF (MHz) min.	DCR (Ω) max.	IDC (mA) max.	Colour Code		
								1st	2nd	3rd
MCFT000165	0.22	±5, ±10%	35	25.2	800	0.15	2600	Red	Red	Brown
MCFT000167	0.47	±10%	35	25.2	460	0.2	2400	Yellow	Violet	Brown
MCFT000168	0.68	±5, ±10%	35	25.2	400	0.3	1700	Blue	Gray	Brown
MCFT000169	1	±10%	22	7.96	245	0.35	800	Brown	Black	Red
MCFT000170	1.5	±5, ±10%	25	7.96	182	0.45	550	Brown	Green	Red
MCFT000171	2.2	±5, ±10%	22	7.96	105	0.6	500	Red	Red	Red
MCFT000172	3.3	±5, ±10%	22	7.96	55	0.75	450	Orange	Orange	Red
MCFT000173	4.7	±5, ±10%	22	7.96	45	0.9	400	Yellow	Violet	Red
MCFT000174	6.8	±5, ±10%	22	7.96	40	1.05	400	Blue	Gray	Red
MCFT000175	10	±5, ±10%	20	2.52	35	1.55	300	Brown	Black	Orange
MCFT000176	15	±5, ±10%	20	2.52	24	2.38	250	Brown	Green	Orange
MCFT000177	22	±5, ±10%	20	2.52	18	2.92	200	Red	Red	Orange
MCFT000178	33	±5, ±10%	20	2.52	16	4.1	180	Orange	Orange	Orange
MCFT000179	47	±5, ±10%	23	2.52	17	7.8	350	Yellow	Violet	Orange
MCFT000181	100	±5, ±10%	13	1	4	13.2	200	Brown	Black	Yellow

Wire Wound Chip Inductor Ferrite

multicomp PRO

1210 Wire Wound Chip Inductors (Ferrite / Molding Type) / Large Current Type

Part Number	Inductance (μH)	Tolerance	Q min.	Test Freq. (MHz)	SRF (MHz) min.	DCR (Ω) max.	IDC (mA) max.
MCFT000182	1	±20%	10	7.96	100	0.156	770
MCFT000183	1.5	±20%	10	7.96	80	0.195	580
MCFT000184	2.2	±20%	10	7.96	65	0.26	480
MCFT000184	3.3	±20%	10	7.96	55	0.325	400
MCFT000186	4.7	±20%	10	7.96	45	0.52	320
MCFT000187	6.8	±20%	10	7.96	35	0.65	280
MCFT000188	10	±10%	15	2.52	28	1.105	220
MCFT000189	15	±10%	15	2.52	25	1.69	180
MCFT000190	22	±10%	15	2.52	20	2.6	145
MCFT000191	33	±10%	15	2.52	15	3.64	115
MCFT000192	47	±10%	20	2.52	13	5.46	105
MCFT000193	68	±10%	20	2.52	10	8.45	85
MCFT000194	100	±10%	20	0.796	8	10.14	75

Large Current Electrical Specifications:

1812 Wound Chip Inductors (Ferrite / Open Type) / Large Current Type

Codes	Inductance (μH)	Tolerance	Q min.	Test Freq. (MHz)	SRF (MHz) min.	DCR (Ω) max.	IDC (mA) max.
MCFT000197	1	±10%	10	7.96	200	0.11	1,050
MCFT000198	1.5	±10%	10	7.96	130	0.15	950
MCFT000199	2.2	±10%	10	7.96	80	0.18	850
MCFT000200	3.3	±10%	10	7.96	45	0.22	750
MCFT000201	4.7	±10%	10	7.96	35	0.27	650
MCFT000202	6.8	±10%	10	7.96	28	0.35	600
MCFT000203	10	±10%	10	2.52	22	0.5	550
MCFT000204	15	±10%	10	2.52	20	0.7	450
MCFT000205	22	±10%	10	2.52	18	0.9	370
MCFT000206	33	±10%	10	2.52	14	1.4	300
MCFT000207	47	±10%	10	2.52	11.5	1.9	260
MCFT000208	68	±10%	10	2.52	10	2.6	220
MCFT000209	100	±10%	20	0.796	8	4	180
MCFT000210	150	±10%	20	0.796	7	6.5	140
MCFT000211	220	±10%	20	0.796	5.5	9	120
MCFT000212	330	±10%	20	0.796	4	13	90
MCFT000213	470	±10%	20	0.796	3.5	26	75
MCFT000214	680	±10%	20	0.796	2.6	40	65

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO

Wire Wound Chip Inductor Ferrite



Environmental Characteristics:

Electrical Performance Test

Item	Requirement	Test Method
Inductance	Refer to standard electrical characteristic spec.	HP4291 or HP4284
Q		HP4291 or HP4284
SRF		HP4291
DC Resistance DCR		Agilent 34401A
Rated Current IDC		Applied the current to coils, The inductance change should be less than 10% to initial value

Mechanical Performance Test

Item	Requirement	Test Method
Solderability	The electrodes shall be at least 90% covered with new solder coating	Lead-free inductor: after fluxing(alpha 100 or equiv), inductor shall be dipped in a melted solder bath at 245±5°C, 5±0.5 seconds
Resistance to Soldering Heat	Appearance: No damage	Pre-heating: 150°C, 1min. Solder Temperature: 260±5°C Immersion Time: 10±1 seconds
Vibration	Appearance: No damage L change: within±10% Q change: within±30% DCR: within specification	Test device shall be soldered on the substrate Oscillation Frequency: 10 to 55 to 10Hz for 1 min. Amplitude: 1.5mm Time: 2 hrs for each axis (X, Y & Z), total 6 hrs

Climatic Test

Item	Requirement	Test Method															
Temperature Cycle	Appearance: No damage L change: within±10% Q change: within±30% DCR: within specification	One cycle: <table border="1"> <thead> <tr> <th>Step</th> <th>Temperature (°C)</th> <th>Time (min.)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>-25±3</td> <td>30</td> </tr> <tr> <td>2</td> <td>25±2</td> <td>3</td> </tr> <tr> <td>3</td> <td>85±3</td> <td>30</td> </tr> <tr> <td>4</td> <td>25±2</td> <td>3</td> </tr> </tbody> </table>	Step	Temperature (°C)	Time (min.)	1	-25±3	30	2	25±2	3	3	85±3	30	4	25±2	3
Step		Temperature (°C)	Time (min.)														
1		-25±3	30														
2		25±2	3														
3	85±3	30															
4	25±2	3															
Damp Heat with Load	Total: 100 cycles Measured after exposure in the room condition for 24hrs	Temperature: 40±2°C Relative Humidity: 90 to 95%; Time: 1,000hrs Measured after exposure in the room condition for 24hrs															
High Temperature Storage		Temperature: 85±3°C Applied Current: Rated Current Time: 1,000hrs Measured after exposure in the room condition for 24hrs															
Low Temperature Storage		Temperature: -25±3°C Time: 1,000hrs Measured after exposure in the room condition for 24hrs															


Wire Wound Chip Inductor Ferrite

multicomp PRO

Storage Temperature : 25±3°C; Humidity <80%RH
 Operating Temperature Range : -40°C to +85°C


Packaging:

Packaging Quantity & Reel Specifications



Type	A	B	C	W	T	Quantity (EA)
MCNL05	178±2	60±0.5	13±0.3	9±0.3	12±1	2,000
MCNL08	178±2	60±0.5	13±0.3	9±0.3	12±1	2,000
MCNL10	178±2	60±0.5	13±0.3	9±0.3	12±1	2,000
MCNL12	178±2	80±0.5	13±0.3	13.2±0.3	16±1	500


Embossed Plastic Tape Specifications:



Type	A	B	C	D	E	F	G	H	J
MCNL05	8	1.85	4	2.55	3.5	1.75	2	1.45	0.23
MCNL08	8	2.8	4	2.95	3.5	1.75	2	2.22	0.23
MCNL10	8	2.96	4	3.6	3.5	1.75	2	2.4	0.23
MCNL12	12	3.3	8	5	5.5	1.75	2	3.5	0.3

Dimensions : Millimetres

Leader / Trailer Tape:




Cover Tape Peel Strength:

The force for tearing off cover tape is 0.1 to 0.6 (N) in the arrow direction at the following conditions:

Temperature : 5°C to 35°C

Humidity : 45% to 85%

Atmospheric pressure : 860 to 1,060hpa




Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 Element14.com/multicomp-pro

multicomp PRO

Wire Wound Chip Inductor Ferrite

multicomp PRO

Reflow:



Part Number Table

Description	Part Number
Inductor, Ferrite, 0805, 0.15 μ H	MCFT000152
Inductor, Ferrite, 0805, 0.22 μ H	MCFT000153
Inductor, Ferrite, 0805, 0.33 μ H	MCFT000154
Inductor, Ferrite, 0805, 0.47 μ H	MCFT000155
Inductor, Ferrite, 0805, 0.68 μ H	MCFT000156
Inductor, Ferrite, 0805, 1 μ H	MCFT000157
Inductor, Ferrite, 0805, 1.5 μ H	MCFT000158
Inductor, Ferrite, 0805, 2.2 μ H	MCFT000159
Inductor, Ferrite, 0805, 3.3 μ H	MCFT000160
Inductor, Ferrite, 0805, 4.7 μ H	MCFT000161
Inductor, Ferrite, 0805, 6.8 μ H	MCFT000162
Inductor, Ferrite, 0805, 10 μ H	MCFT000163
Inductor, Ferrite, 1008, 0.22 μ H	MCFT000165
Inductor, Ferrite, 1008, 0.33 μ H	MCFT000166
Inductor, Ferrite, 1008, 0.47 μ H	MCFT000167
Inductor, Ferrite, 1008, 0.68 μ H	MCFT000168
Inductor, Ferrite, 1008, 1 μ H	MCFT000169
Inductor, Ferrite, 1008, 1.5 μ H	MCFT000170
Inductor, Ferrite, 1008, 2.2 μ H	MCFT000171
Inductor, Ferrite, 1008, 3.3 μ H	MCFT000172
Inductor, Ferrite, 1008, 4.7 μ H	MCFT000173
Inductor, Ferrite, 1008, 6.8 μ H	MCFT000174
Inductor, Ferrite, 1008, 10 μ H	MCFT000175

Description	Part Number
Inductor, Ferrite, 1008, 15 μ H	MCFT000176
Inductor, Ferrite, 1008, 22 μ H	MCFT000177
Inductor, Ferrite, 1008, 33 μ H	MCFT000178
Inductor, Ferrite, 1008, 47 μ H	MCFT000179
Inductor, Ferrite, 1008, 68 μ H	MCFT000180
Inductor, Ferrite, 1008, 100 μ H	MCFT000181
Inductor, Ferrite, 1210, 1 μ H	MCFT000182
Inductor, Ferrite, 1210, 1.5 μ H	MCFT000183
Inductor, Ferrite, 1210, 2.2 μ H	MCFT000184
Inductor, Ferrite, 1210, 3.3 μ H	MCFT000185
Inductor, Ferrite, 1210, 4.7 μ H	MCFT000186
Inductor, Ferrite, 1210, 6.8 μ H	MCFT000187
Inductor, Ferrite, 1210, 10 μ H	MCFT000188
Inductor, Ferrite, 1210, 15 μ H	MCFT000189
Inductor, Ferrite, 1210, 22 μ H	MCFT000190
Inductor, Ferrite, 1210, 33 μ H	MCFT000191
Inductor, Ferrite, 1210, 47 μ H	MCFT000192
Inductor, Ferrite, 1210, 68 μ H	MCFT000193
Inductor, Ferrite, 1210, 100 μ H	MCFT000194
Inductor, Ferrite, 1210, 150 μ H	MCFT000195
Inductor, Ferrite, 1812, 1 μ H	MCFT000197
Inductor, Ferrite, 1812, 1.5 μ H	MCFT000198
Inductor, Ferrite, 1812, 2.2 μ H	MCFT000199

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO

Wire Wound Chip Inductor Ferrite

multicomp PRO

Description	Part Number
Inductor, Ferrite, 1812, 3.3 μ H	MCFT000200
Inductor, Ferrite, 1812, 4.7 μ H	MCFT000201
Inductor, Ferrite, 1812, 6.8 μ H	MCFT000202
Inductor, Ferrite, 1812, 10 μ H	MCFT000203
Inductor, Ferrite, 1812, 15 μ H	MCFT000204
Inductor, Ferrite, 1812, 22 μ H	MCFT000205
Inductor, Ferrite, 1812, 33 μ H	MCFT000206
Inductor, Ferrite, 1812, 47 μ H	MCFT000207

Description	Part Number
Inductor, Ferrite, 1812, 68 μ H	MCFT000208
Inductor, Ferrite, 1812, 100 μ H	MCFT000209
Inductor, Ferrite, 1812, 150 μ H	MCFT000210
Inductor, Ferrite, 1812, 220 μ H	MCFT000211
Inductor, Ferrite, 1812, 330 μ H	MCFT000212
Inductor, Ferrite, 1812, 470 μ H	MCFT000213
Inductor, Ferrite, 1812, 680 μ H	MCFT000214

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO