



### Main

Product or component type	Dimmer
Local signalling	On: indicator light, LED (amber) Off: indicator light, LED (blue)
Additional information	With memory push
[Ue] rated operational voltage	220...240 V AC 50 Hz
Material	Brass: metal parts Polycarbonate: plastic part Steel: metal parts
Cover frame colour tint	Silver bronze

### Complementary

Wiring device mounting	Surface Flush
Clamping connection capacity	2 x 4 mm <sup>2</sup> for solid cable(s) 2 x 4 mm <sup>2</sup> for stranded cable(s) 3 x 2.5 mm <sup>2</sup> for solid cable(s) 3 x 2.5 mm <sup>2</sup> for stranded cable(s)
Rated operational power in VA	350 VA
Number of gangs	1 gang
Load type	LV halogen Incandescent lamp
Embedding depth	6 mm
Width	87 mm
Height	87 mm
Depth	35 mm

### Environment

Maximum ambient air temperature for operation	40 °C
Relative humidity	10...95 %
Ambient air temperature for storage	0...60 °C
Standards	IEC 60669-2-1

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm
Package 1 Weight	127.03 g
Unit Type of Package 2	BB1
Number of Units in Package 2	6
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	901.5 g
Unit Type of Package 3	CAR

Number of Units in Package 3	60
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	9015 g

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------