



### Main

Range	ZENcelo
Product or component type	Telephone + data socket
Device application	Communication
Socket additional information	Shuttered
Colour tint	Silver satin

### Complementary

Communication network category	Voice: 3 Data: 5e
Insulation resistance	>= 200 MOhm
Number of gangs	2 gangs
Contacts material	Contact: phosphor bronze with gold plating IDC contact: phosphor bronze with nickel plating
Material	Polycarbonate plastic part
Device mounting	Surface Flush
Width	87 mm
Height	87 mm
Depth	36 mm
Embedding depth	30.2 mm

### Environment

AWG gauge	AWG 34...AWG 23 (4 twisted pair cables)
Dielectric strength	1000 V for 60 s at 60 Hz
Ambient air temperature for operation	0...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Standards	ASTMD4566-98 TIA/EIA-568-B.2-1

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3 cm
Package 1 Width	8.72 cm
Package 1 Length	8.72 cm
Package 1 Weight	129.16 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm

Package 2 Weight	1.233 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	12832.8 g