



Main

| | |
|---------------------------|--------------------------|
| Range | Pieno |
| Product or component type | Switch |
| Device application | Control |
| Switch application | Switch |
| Load type | Resistive Fluorescent |
| Cover frame colour tint | Wine gold |

Complementary

| | |
|------------------------------|---|
| Device mounting | Surface Flush |
| Switch function | 2-way |
| Number of rocker | 2 |
| Rated current | 16 AX at 250 V AC 50 Hz |
| Local signalling | Fluorescent |
| Material | Polycarbonate: surround Polycarbonate: grid plate |
| Connections - terminals | Pillar terminals |
| Clamping connection capacity | 2 x 1.5 mm ² for stranded cable(s) 2 x 2.5 mm ² for solid cable(s) |
| Embedding depth | 23 mm |
| Width | 87 mm |
| Height | 87 mm |
| Depth | 23 mm |

Environment

| | |
|---------------------------------------|--|
| Ambient air temperature for operation | -5...40 °C |
| Relative humidity | 0...95 % |
| Standards | IEC 60669-1 SS 227-1 MS IEC 60669-1 GB 16915.1 BS EN 60669-1 |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.55 cm |
| Package 1 Width | 8.7 cm |
| Package 1 Length | 8.7 cm |
| Package 1 Weight | 99.67 g |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant with Exemptions |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |