Product data sheet Characteristics

E8231RJS_5_LS

1G RJ45 Data Outlet, Cat 5e, Keystone on Shuttered Wallplate, Lavender Silver





Main	
Product or component type	Data socket
Communication network category	5e
Number of gangs	1 gang
Cover frame colour tint	Lavender silver

Complementary

Wiring device mounting	Surface Flush	
Material	Polycarbonate: surround Polycarbonate: grid plate	
Connections - terminals	RJ45 connector	
Width	87 mm	
Height	87 mm	
Depth	38.8 mm	

Environment

Ambient air temperature for operation	-540 °C
Relative humidity	095 %
Standards	IEC 60670 GB 17466

Packing Units

racking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.56 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	65.3 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.5 cm
Package 2 Width	19 cm
Package 2 Length	19.5 cm
Package 2 Weight	749 g
Unit Type of Package 3	S04
Number of Units in Package 3	80
Package 3 Height	30 cm
Package 3 Width	40 cm
Package 3 Length	60 cm
Package 3 Weight	7.81 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherenced as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation is not be used to perform the appropriate and complete risk analysis, evaluation of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

Contractual warranty

Warranty	18 months