Heavy Duty Connector Inserts Axial Module



200A, 1000V, 1 Pin, Insert

RoHS Compliant



Specifications

 Rated Current
 : 200A

 Rated Voltage
 : 1000V

 Rated Impulse Voltage
 : 8KV

 Pollution Degree
 : 3

 Insulation Resistance
 : ≥10 10 Ω

Material : Polycarbonate
Temperature Range : -40°C to +125°C

Mating Cycles : ≥500

Contact Material : Copper Alloy

Contact Surface : Silver plated / Gold plated


 Contact Resistance
 : ≤0.2mΩ

 Wire Gauge
 : 25~70mm²

 AWG
 : 2-0

 Stripping Length
 : 16mm

Diagram



Dimensions: Millimetres

Part Number Table

Description	Part Number
Heavy Duty Connector Insert, 200A, 1000V, 1 Pin, Female, Screw Terminal, 25~40mm ²	MP009470
Heavy Duty Connector Insert, 200A, 1000V, 1 Pin, Male, Screw Terminal, 25~40mm²	MP009471
Heavy Duty Connector Insert, 200A, 1000V, 1 Pin, Female, Screw Terminal, 40~70mm ²	MP009472
Heavy Duty Connector Insert, 200A, 1000V, 1 Pin, Male, Screw Terminal, 40~70mm ²	MP009473

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro



14/04/22 V1.0