



1059-VXL

3/8" VIBROTHERM DRIVE COMPOSITE COMPACT IMPACT WRENCH

FEATURES

- Provides 550 ft-lb maximum torque and 750 ft-lb of loosening torque
- VIBROTHERM DRIVE® impact wrenches incorporate the new patented AIRCAT design impact wrench mechanism
- The new mechanism reduces vibration levels by 30%-40% and increases the life of the mechanism by 50%
- The latest patented AIRCAT muffler system provides the AIRCAT's unmatched low noise levels
- The patented grip design provides the customary AIRCAT operator comfort
- Investment in tooling, materials, and the triple injection molding processes enables AIRCAT® to produce cosmetic designs that are unmatched in the industry

SPECIFICATIONS

Loosening Torque (ft-lb) @90psi	750
Square Drive (in.)	3/8
Bolt Capacity (in.)	9/16
Free Speed (RPM)	9,000
Impacts Per Minute (IPM)	1,700
Weight (lbs.)	2.8
Length (in.)	4.4
Noise Level d(B)A	82
Vibration Level (m/sec ²)	4.3
Rec. Hose Size (in.)	3/8
Air Inlet (in.) NPT/BSP	1/4

VIBROTHERM
by **AIRCAT DRIVE®**



Styled for perfection and built to last!

AIRCAT

a Division of Florida Pneumatic Manufacturing Corporation
851 Jupiter Park Lane / Jupiter, Florida 33458

www.AIRCAT.com

(800) 356-3392