65W Multi Head Wall Plug Adapter Multicomp PRO

Features

- Interchangeable AC Heads
- DOE Level VI Efficiency
- Overcurrent Protection
- Short Circuit Protection
- 1 Year Warranty

Compliant

RoHS


· DC Cable Length: 1500mm

	Models	MP009248	MP009249	
Output	DC Voltage	12V DC	24V DC	
	Rated Current	5amp	2.5amp	
	Current Range	0-5amp	0-2.5amp	
	Rated Power	60 Watt		
	Ripple & Noise	240mVp-p max		
	Output Regulation	±5%		
	Output Connector	2.1 × 5.5 × 12mm C+ve		
Input	Voltage Range	90V AC to 264V AC		
	Frequency Range	47Hz to 63Hz		
	Input Current	1.2amp Max		
	Inrush Current	40amp Max		
	Standby Power	0.1W Max		
	Leakage Current	0.25amp Max		
	Input Connector	UK, EU, US & AUS AC Heads		
Environment	Operating Temp	0°C to 40°C		
	Cooling	Convection		
	Temperature Coefficient	0.05%/°C		
	Humidity	5~95%RH(non-condensing)		
	Storage Temp	-20°C to	-20°C to +80%°C	
Safety & EMC	Safety Standards	UL/CUL 62368-1, GS/TUV EN	UL/CUL 62368-1, GS/TUV EN62368-1, SAA AS/NZ 61558.2	
	EMC Emissions	EN55032,EN55035,	EN55032,EN55035, FCC Part 15 Class B	

Mechanical Specification

Dimensions: Millimetres

Specification



Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro



Page <1> 12/07/22 V1.1

AU AC PLUG

EU AC PLUG