



Datasheet

RS PRO SUCTION & DISCHARGE HOSE ASSEMBLIES

Stock number: See Table





Medium Duty Suction & Delivery Hose Assemblies

A medium weight PVC hose, reinforced with a rigid crush and kink resistant internal white PVC helix. It is tough, flexible and extremely durable. It has outstanding resistance to the effects of weather. Minimum frictional loss is achieved by the smooth bore.

Key Features

- Tough, flexible and extremely durable even under cold working conditions.
- · Outstanding resistance to the effects of weather.
- · Excellent chemical and abrasion resistance.

Application examples:

- Suction and discharge of water, slurry, sewage, powders and semi-liquid products
- Agricultural
- Construction
- · General manufacturing industries
- · Higher vacuum applications

Medium Duty Suction				
Camlock Couplings	Diameter	Length		
1860525	2"	6m		
1860526	3"	6m		
1860527	4"	6m		
	Camlock Couplings 1860525 1860526	Camlock Couplings Diameter 1860525 2" 1860526 3"		

External Spiral Suction Hose Assemblies

Medium duty elastic quality suction hose with an external crush resistant helix. The exposed outer helix has excellent abrasion resistance and minimises drag resistance. Tough, flexible and extremely durable even under very cold working conditions. Excellent resistance to weather. Suitable for suction and discharge of water, slurries, liquid sewage and dilute chemicals.

Key Features

- Tough, flexible and extremely durable even under very cold working conditions.
- · Optimum flow is maintained by the smooth bore.
- Heavy duty external helix offers improved abrasion resistance and shock resistant properties.
- · Excellent chemical and abrasion resistance.

Application examples:

- · Suction and delivery of water, sewage, slurries and powders
- Construction
- General manufacturing industries
- Agricultural tanker applications

External Spiral Suction				
Leverlock Couplings	Camlock Couplings	Diameter	Length	
1860528	1860531	2"	6m	
1860529	1860532	3"	6m	
1860530	1860533	4"	6m	