

ACF504

Roof Fan Tray 208/230VAC 50/60HZ for NetShelter SX 750mm Wide x 1070mm Deep Enclosures



Overview

Presentation	The Rack Fan Tray is a low cost solution that aids in heat removal from a Netshelter Enclosure. The system easily installs into the top of the enclosure and expels heat from the roof of the rack. Wall-mounted enclosures have the additional option of installing the rack fan tray systems in the base of the rack as well. The fan trays are designed to promote bottom to top airflow within the enclosure.
Lead time	Usually in Stock

Main

Main Input Voltage	208 V 230 V
Input Connection Type	IEC 60320 C14 Schuko CEE 7/7P BS 1363A British
Number of cables	1
Provided equipment	Installation guide

Physical

Colour	Black
Height	6 cm
Width	72.4 cm
Depth	89.3 cm
Net weight	10.23 kg
Mounting preference	No preference
Mounting mode	Rack-mounted

Input

Network frequency	50/60 Hz
-------------------	----------

Conformance

Product certifications	PSE
Standards	CSA C22.2 No 60950 UL 60950

Environmental

Air flow	207.66 l/s
Audible noise at 1 meter from surface of unit	62 dBA

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.5 cm
Package 1 Width	99.1 cm
Package 1 Length	91.4 cm
Package 1 Weight	14 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------