


## RC series Single-Acting General Purpose Cylinder



Capacity:5~100T  
Stroke:16~362mm  
Maximum Operating Pressure:700bar



### RC Series Selection Chart

Stock Code	Model	Capacity (Ton)	Stroke (mm)	Min Height (mm)	Outside Diameter (mm)	Effective Area (cm <sup>2</sup> )	Oil Capacity (cm <sup>3</sup> )	Saddle Diameter (mm)	Thread Size (mm)	Thread Length (mm)	Weight (Kg)
AQ00326-K	RC-50	5	16	41	42x59	6.5	10	25.4	1 1/2"-16	28	1.1
AQ00327-K	RC-51	5	25	110	38	6.5	16	25.4	1 1/2"-16	28	1.1
AQ00328-K	RC-53	5	76	165	38	6.5	50	25.4	1 1/2"-16	28	1.5
AQ00329-K	RC-55	5	127	215	40	6.5	83	25.4	1 1/2"-16	28	1.9
AQ00330-K	RC-57	5	177	273	40	6.5	115	25.4	1 1/2"-16	28	2.4
AQ00331-K	RC-59	5	232	323	40	6.5	151	25.4	1 1/2"-16	28	2.8
AQ00332-K	RC-101	10	26	89	57	14.5	38	38.1	2 1/4"-14	27	1.8
AQ00333-K	RC-102	10	54	121	57	14.5	78	38.1	2 1/4"-14	27	2.3
AQ00334-K	RC-104	10	105	171	57	14.5	152	38.1	2 1/4"-14	27	3.3
AQ00335-K	RC-106	10	156	247	57	14.5	226	38.1	2 1/4"-14	27	4.4
AQ00336-K	RC-108	10	203	298	57	14.5	294	38.1	2 1/4"-14	27	5.4
AQ00337-K	RC-1010	10	257	349	57	14.5	373	38.1	2 1/4"-14	27	6.4
AQ00338-K	RC-1012	10	304	400	57	14.5	441	38.1	2 1/4"-14	27	6.8
AQ00339-K	RC-1014	10	356	450	57	14.5	516	38.1	2 1/4"-14	27	8.2
AQ00340-K	RC-151	15	25	124	69	20.3	51	41.4	2 3/4"-16	30	3.3
AQ00341-K	RC-152	15	51	149	69	20.3	104	41.4	2 3/4"-16	30	4.1
AQ00342-K	RC-154	15	101	200	69	20.3	205	41.4	2 3/4"-16	30	5.0
AQ04890-K	RC-156	15	152	271	69	20.3	308	41.4	2 3/4"-16	30	6.8
AQ00343-K	RC-158	15	203	322	69	20.3	411	41.4	2 3/4"-16	30	8.2
AQ00344-K	RC-1510	15	254	373	69	20.3	516	41.4	2 3/4"-16	30	9.5
AQ04891-K	RC-1512	15	305	423	69	20.3	619	41.4	2 3/4"-16	30	10.9
AQ04892-K	RC-1514	15	356	474	69	20.3	723	41.4	2 3/4"-16	30	11.8
AQ00345-K	RC-251	25	26	139	85	33.2	86	57.2	3 5/16"-12	49	5.9
AQ00346-K	RC-252	25	50	165	85	33.2	166	57.2	3 5/16"-12	49	6.4
AQ00347-K	RC-254	25	102	215	85	33.2	339	57.2	3 5/16"-12	49	8.2
AQ00348-K	RC-256	25	158	273	85	33.2	525	57.2	3 5/16"-12	49	10.0
AQ00349-K	RC-258	25	210	323	85	33.2	697	57.2	3 5/16"-12	49	12.2
AQ00350-K	RC-2510	25	261	374	85	33.2	867	57.2	3 5/16"-12	49	14.1
AQ04893-K	RC-2512	25	311	425	85	33.2	1033	57.2	3 5/16"-12	49	16.3
AQ00351-K	RC-2514	25	362	476	85	33.2	1202	57.2	3 5/16"-12	49	17.7
AQ00352-K	RC-308	30	209	387	101	42.1	880	57.2			18.1
AQ00353-K	RC-502	50	51	176	127	71.2	362	79.5	5"-12	55	15.0
AQ00354-K	RC-504	50	101	227	127	71.2	719	79.5	5"-12	55	19.1
AQ00355-K	RC-506	50	159	282	127	71.2	1131	79.5	5"-12	55	23.1
AQ00356-K	RC-5013	50	337	460	127	102.6	2399	79.5	5"-12	55	37.6
AQ00357-K	RC-756	75	156	285	146	71.2	1601	95.2			29.5
AQ04894-K	RC-7513	75	333	492	146	102.6	3417	95.2			59.0
AQ00358-K	RC-1006	100	168	357	177	133.3	2239	104.9			59.0
AQ00359-K	RC-10010	100	260	449	177	133.3	3466	104.9			72.6