XAPA3100

Empty control station without hinges, Harmony XAP, XB2 SL, plastic, grey, undrilled, 151x241x87mm





Main

Range of product	Harmony XAP
Product or component type	Empty control station without hinges
Device short name	XAPA
Product front plate size	151 x 241 mm
Usable depth	83 mm
Number of cut-out	Undrilled
Colour of base of enclosure	Grey
Colour of cover	Grey
Material	Glass reinforced polyester
Cable entry	Undrilled
Device mounting	Flush
IP degree of protection	IP65 conforming to IEC 60529 IP69 conforming to NF C 20-010 IP69K
Resistance to chemical agents	High resistant to acids High resistant to all solvents High resistant to bases High resistant to diesel High resistant to mineral salts High resistant to oils and greases High resistant to petrol High resistant to sea water

Complementary

Complementary		
Net weight	0.86 kg	
Flame retardance	M3 conforming to CSTB	
	VO conforming to UL 94	

Environment

Protective treatment	TH			
	TC			
Ambient air temperature for storage	-4070 °C			
Ambient air temperature for operation	-4070 °C			
Overvoltage category	Class II conforming to IEC 60536 Class II conforming to NF C 20-030			
Fire resistance	850 °C conforming to NF C 20-455 960 °C conforming to IEC 92			

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	13 cm	
Package 1 Width	16.6 cm	
Package 1 Length	24.5 cm	
Package 1 Weight	1.032 kg	
Unit Type of Package 2	S03	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent or and is not to be used for determining suitability or inhability of these products for specific user applications. It is the dourn and resting of the products with respect to the relevant specific application or use thereof. It is the duty of any contribution or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Number of Units in Package 2	4
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.616 kg
Unit Type of Package 3	P06
Number of Units in Package 3	32
Package 3 Height	77 cm
Package 3 Width	80 cm
Package 3 Length	60 cm
Package 3 Weight	45.38 kg


Offer Sustainability

Sustainable offer status	Green Premium product				
REACh Regulation	REACh Declaration				
REACh free of SVHC	Yes				
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)				
Toxic heavy metal free	Yes				
Mercury free	Yes				
China RoHS Regulation	China RoHS Declaration				
RoHS exemption information	€Yes				
Environmental Disclosure	Product Environmental Profile				
Circularity Profile	No need of specific recycling operations				

Contractual warranty

Warranty	18 months

Dimensions and Fixing



(2) 2 x Ø 5.6 mm/4.94 in. holes, depth 12 mm/0.47 in. P Usable depth

а		b		G		Н	
mm	in.	mm	in.	mm	in.	mm	in.
151	5.94	241	9.49	135	5.31	200	7.87