

Datasheet

RS Pro Multi Function 5 Time Delay Relay, Screw, 0.1 s → 10 h, SPDT, 1 Contacts, SPCO, 24 → 240 V ac/dc

RS Stock No: **896-6850**



Product Details

RS Pro multi function 5 time delay relay is made to a high degree of precision and accuracy. The time settings can be set easily by using the knob on the front of the time delay relay. It comes with a terminal screw type and has, a time range of 0.1 s to 10 h with SPDT and SPCO switch and contact configuration. It has 1 contact and supply voltage of 24 to 240 V ac/dc.

Features and Benefits

- Multifunction - 10 different modes
- 17.5 mm wide
- DIN rail mounting
- LED indications for power and relay status
- SPCO output relay
- 100 ms - 100 hours timing range
- IP20 (terminals), IP40 (enclosure) protection
- Wide voltage range

Specifications:

Number of Timer Functions	5
Power Supply	External
Switch Configuration	SPCO
Time Increment	Seconds
Depth	100.5 mm
Length	75 mm
Maximum Operating Temperature	+60°C
Minimum Operating Temperature	-15°C
Number of Contacts	1
Width	22.5 mm
Contact Configuration	CO
Current Maximum	5 A
Current Minimum	0.1 A
Maximum Voltage	240 V ac/dc
Minimum Voltage	24 V ac/dc
Mode of Operation	Multi Function
Mounting Type	DIN Rail
Supply Voltage	24 to 240 V ac/dc
Terminal Type	Screw
Time Delay	200 ms
Time Range	0.1 s to 10 h
IP Rating	IP20, IP40